

Re: [RFC] Initialisation of ssh-agent

Source: <http://linux.derkeiler.com/Mailing-Lists/Debian/2003-07/0290.html>

From: Ryan Nowakowski (*tubaman_at_mailandnews.com*)

Date: 07/23/03

Date: Wed, 23 Jul 2003 10:47:48 -0500

To: debian-user@lists.debian.org

The way that is usually handled is when the process starts, you record the pid in a file in /var/run or /tmp. Then you grab the pid from that file when you need to check it.

- Ryan

On Wed, Jul 23, 2003 at 09:27:36AM +0100, Colin Watson wrote:

> *On Sat, Jul 19, 2003 at 07:07:19PM +0200, HdV@DTO.TUdelft.NL wrote:*

> > *Finally there is the output of "ps ux". I use it to verify the PID of*
> > *the ssh-agent process. For that I take the value found in the second*
> > *column, but I am not sure if "ps ux" will give me that on all/most*
> > *unices. Does anyone on the list know?*

>

> *ps is probably the most inconsistent command in the entirety of Unix.*
> *No, 'ps ux' won't work on Unix systems which take most of their heritage*
> *from System V rather than BSD, and there is probably no one set of ps*
> *arguments that will work everywhere.*

>

> *Cheers,*

>

> --

> *Colin Watson [cjwatson@flatline.org.uk]*

>

>

> --

> *To UNSUBSCRIBE, email to debian-user-request@lists.debian.org*

> *with a subject of "unsubscribe". Trouble? Contact listmaster@lists.debian.org*

>

--

To UNSUBSCRIBE, email to debian-user-request@lists.debian.org

with a subject of "unsubscribe". Trouble? Contact listmaster@lists.debian.org

Debian-User: Re: [RFC] Initialisation of ssh-agent

- application/pgp-signature attachment: stored