

Re: "Sxxxx"s and "Kxxxx"s in /etc/rc(*)d/

Re: "Sxxxx"s and "Kxxxx"s in /etc/rc(*)d/

Source: <http://linux.derkeiler.com/Mailing-Lists/Debian/2006-02/msg03313.html>

- *From:* Deephay <todoxxx@xxxxxxxxxx>
 - *Date:* Tue, 28 Feb 2006 23:18:30 +0800
-

Hi all,

I've found the reason. I wrote a line in the /etc/ppp/ip-up.d/ to bring up ntpd whenever the ppp interface is brought up. thx for your help!

Deephay

On 2/28/06, Juergen Fiedler <juergen@xxxxxxxxxxxxxxxxxx> wrote:

On Tue, Feb 28, 2006 at 10:00:00PM +0800, Deephay wrote:

Greetings all,

I read the debian references and there are some sentences like

this:

"scripts whose names begin with K are run with the argument stop.
Scripts beginning with S are run with the argument start."
So, the corresponding services whose names begin with K will not be started? But I have a K23ntp-server in my /etc/rc(2-5).d/ , it will

be

started though. Anyone can tell me why? thx!

Deephay

Do you, by any chance, also have a SXXntp-server in those directories?
If you do, that might do that.

--j

-----BEGIN PGP SIGNATURE-----
Version: GnuPG v1.4.1 (GNU/Linux)

Re: "Sxxxx"s and "Kxxxx"s in /etc/rc(*)d/

Re: "Sxxxx"s and "Kxxxx"s in /etc/rc(*)d/

iD8DBQFEBFnohqmlHrBtR3kRAqL0AJ99Sob+SG31KYIH9XH+Nu3Od/x53wCghGzB
CDUkSI4kWMw9uQxpJdsXCL8=
=JdUB
-----END PGP SIGNATURE-----