

Re: fetchmail and not delivering cc + bcc mail

Source: <http://linux.derkeiler.com/Mailing-Lists/Fedora/2006-10/msg04140.html>

- *From:* Keith <ac7xcLnx@xxxxxxxxxxx>
 - *Date:* Tue, 31 Oct 2006 05:35:48 -0800
-

On Tue, 2006-10-31 at 12:41 +0200, Gregory Machin wrote:

Hi
Please could you advise.
I have fetchmail / sendmail running on a server that collects mail every 15 min, but it seems that the mail address in the cc and bcc are not being delivered to the user's boxes and going to the catch all box.
What could be wrong ...

--
Gregory Machin
gregory.machin@xxxxxxxxxx
www.linuxpro.co.za

Create a procmail recipe to deliver the mail to the user mailbox.
If fetchmail is being run by root then put a .fetchmailrc in root's directory or you can set one up in /etc. If it is a user account you are running fetchmail create a .fetchmailrc in the users directory. The most important line is to use

is localuseraccountname here

sample .fetchmailrc

```
set postmaster "username"  
set logfile .mailfetch-log
```

```
poll mail.servername.net with proto POP3 uidl  
user 'pop3_username'  
pass 'pop3_password'  
is localuseraccountname here  
keep
```

```
## end of .fetchmailrc
```

Re: fetchmail and not delivering cc + bcc mail

You can use a .procmailrc recipe to catch anything to a certain pop3_accounts name in the header.

```
:0H:  
* .*pop3_username.*  
/var/spool/mail/username
```

--
BC-246T Control & Programming Tool TCL/TK
<http://home.comcast.net/~kilowattradio/ftp/>
Ham_Scanner SWL Info <http://home.comcast.net/~kilowattradio/>
WindowXP <> Linux Easy Dual Boot
http://home.comcast.net/~kilowattradio/linux/wXP_linux_boot.txt

--
fedora-list mailing list
fedora-list@xxxxxxxxxxx
To unsubscribe: <https://www.redhat.com/mailman/listinfo/fedora-list>

Re: fetchmail and not delivering cc + bcc mail