

# Re: Procmail Regex

---

*Source:* <http://linux.derkeiler.com/Mailing-Lists/Fedora/2007-05/msg01104.html>

---

- *From:* Anne Wilson <[cannewilson@xxxxxxxxxxxxxxx](mailto:cannewilson@xxxxxxxxxxxxxxx)>
  - *Date:* Fri, 11 May 2007 10:27:47 +0100
- 

On Friday 11 May 2007, Anne Wilson wrote:

On Friday 11 May 2007, Linux Geeks wrote:

Hi All,

Right now I have a global account which reside in my ISP's server, and I twice a day get all my emails using fetchmail + cron and delivered them to each mailbox using procmail.

Right now I'm using an abundant rules to check agains 'To' and 'Received' header from incoming mails as shown below

=====

:0

```
* ^To:.+a@domain\.com
! a@xxxxxxxxxxx
```

:0

```
* ^Received:.+a@domain\.com
! a@xxxxxxxxxxx
```

=====

This rule is very inefficient. As I create new user, I have to add two additional rule entry. Is there any regex alternative to my problem ?

Try

:0

```
* (^To|^Received):.+a@domain\.com
! a@xxxxxxxxxxx
```

Re: Procmail Regex

This may be a mixture of methods, so may not work. I use structures like

`${MAILDIR}.INBOX.Design/`

in the destination line.

Anne

***Attachment:*** *pgppWP6Ea2Y2e.pgp*

*Description:* PGP signature

—

fedora-list mailing list

fedora-list@xxxxxxxxxx

To unsubscribe: <https://www.redhat.com/mailman/listinfo/fedora-list>