

## Re: net: generic netdev\_ioaddr

**Source:** <http://linux.derkeiler.com/Mailing-Lists/Kernel/2004-10/10170.html>

---

**From:** Krzysztof Halasa (*khc\_at\_pm.waw.pl*)

**Date:** 10/31/04

To: Pekka Enberg <penberg@cs.helsinki.fi>

Date: Sun, 31 Oct 2004 02:02:48 +0100

Pekka Enberg <penberg@cs.helsinki.fi> writes:

>> *With this driver it happens to be MMIO address.*

Of course 0x4000 was an IO (non-MMIO) address.

> *It seems that the user can also setup dev->base\_addr with "netdev="*  
> *kernel parameter before a driver starts probing (for example*  
> *drivers/net/appletalk/cops.c). Should we get rid of "netdev=" too and*  
> *push preconfiguring down to the drivers that actually use it?*

Sure, cops.io= should be fine. Or cops.hw=io,irq,mem etc.

Still, this is an issue with non-PnP ISA cards only.

--

Krzysztof Halasa

-

To unsubscribe from this list: send the line "unsubscribe linux-kernel" in the body of a message to majordomo@vger.kernel.org

More majordomo info at <http://vger.kernel.org/majordomo-info.html>

Please read the FAQ at <http://www.tux.org/lkml/>