

[2.6 patch] char/cyclades.c: remove unused code

Source: <http://linux.derkeiler.com/Mailing-Lists/Kernel/2004-10/10359.html>

From: Adrian Bunk (*bunk_at_stusta.de*)

Date: 10/31/04

Date: Sun, 31 Oct 2004 22:34:28 +0100

To: async@cyclades.com

The patch below removes unused code from drivers/char/cyclades.c

diffstat output:

```
drivers/char/cyclades.c | 21 -----
1 files changed, 21 deletions(-)
```

Signed-off-by: Adrian Bunk <bunk@stusta.de>

```
--- linux-2.6.10-rc1-mm2-full/drivers/char/cyclades.c.old 2004-10-31 19:49:35.000000000 +0100
```

```
+++ linux-2.6.10-rc1-mm2-full/drivers/char/cyclades.c 2004-10-31 19:52:36.000000000 +0100
```

```
@@ -758,7 +758,6 @@
```

```
 * allocated when the first cy_open occurs.
```

```
 */
```

```
static unsigned char *tmp_buf;
```

```
-DECLARE_MUTEX(tmp_buf_sem);
```

```
/*
```

```
 * This is used to look up the divisor speeds and the timeouts
```

```
@@ -5538,24 +5537,4 @@
```

```
module_init(cy_init);
```

```
module_exit(cy_cleanup_module);
```

```
-#ifndef MODULE
```

```
-/* called by linux/init/main.c to parse command line options */
```

```
-void
```

```
-cy_setup(char *str, int *ints)
```

```
-{
```

```
-#ifdef CONFIG_ISA
```

```
- int i, j;
```

```
-
```

```
- for (i = 0 ; i < NR_ISA_ADDRS ; i++) {
```

```
- if (cy_isa_addresses[i] == 0) break;
```

```
- }
```

```
- for (j = 1; j <= ints[0]; j++){
```

```
- if ( i < NR_ISA_ADDRS ){
```

```
- cy_isa_addresses[i++] = ints[j];
```

```
- }
```

Linux-Kernel: [2.6 patch] char/cyclades.c: remove unused code

```
- }  
-#endif /* CONFIG_ISA */  
-} /* cy_setup */  
-#endif /* MODULE */  
-  
MODULE_LICENSE("GPL");  
-
```

To unsubscribe from this list: send the line "unsubscribe linux-kernel" in
the body of a message to majordomo@vger.kernel.org

More majordomo info at <http://vger.kernel.org/majordomo-info.html>

Please read the FAQ at <http://www.tux.org/lkml/>