

[2.6 patch] drivers/scsi/libata-scsi.c: make some functions static

Source: <http://linux.derkeiler.com/Mailing-Lists/Kernel/2006-01/msg11557.html>

- *From:* Adrian Bunk <bunk@xxxxxxxx>
 - *Date:* Tue, 31 Jan 2006 22:33:01 +0100
-

This patch makes some needlessly global functions static.

Signed-off-by: Adrian Bunk <bunk@xxxxxxxx>

drivers/scsi/libata-scsi.c | 19 ++++++++-----
1 file changed, 9 insertions(+), 10 deletions(-)

--- linux-2.6.15-rc1-mm2-full/drivers/scsi/libata-scsi.c.old 2005-11-20 03:06:38.000000000 +0100

+++ linux-2.6.15-rc1-mm2-full/drivers/scsi/libata-scsi.c 2005-11-20 03:08:34.000000000 +0100

@@ -325,10 +325,10 @@

* RETURNS:

* Command allocated, or %NULL if none available.

*/

```
-struct ata_queued_cmd *ata_scsi_qc_new(struct ata_port *ap,  
- struct ata_device *dev,  
- struct scsi_cmnd *cmd,  
- void (*done)(struct scsi_cmnd *))  
+static struct ata_queued_cmd *ata_scsi_qc_new(struct ata_port *ap,  
+ struct ata_device *dev,  
+ struct scsi_cmnd *cmd,  
+ void (*done)(struct scsi_cmnd *))
```

```
{  
struct ata_queued_cmd *qc;
```

@@ -364,7 +364,7 @@

* LOCKING:

* inherited from caller

*/

```
-void ata_dump_status(unsigned id, struct ata_taskfile *tf)  
+static void ata_dump_status(unsigned id, struct ata_taskfile *tf)  
{
```

```
u8 stat = tf->command, err = tf->feature;
```

@@ -413,8 +413,8 @@

* LOCKING:

[2.6 patch] drivers/scsi/libata-scsi.c: make some functions static

```
* spin_lock_irqsave(host_set lock)
*/
-void ata_to_sense_error(unsigned id, u8 drv_stat, u8 drv_err, u8 *sk, u8 *asc,
- u8 *ascq)
+static void ata_to_sense_error(unsigned id, u8 drv_stat, u8 drv_err,
+ u8 *sk, u8 *asc, u8 *ascq)
{
int i;

@@ -524,7 +524,7 @@
* LOCKING:
* spin_lock_irqsave(host_set lock)
*/
-void ata_gen_ata_desc_sense(struct ata_queued_cmd *qc)
+static void ata_gen_ata_desc_sense(struct ata_queued_cmd *qc)
{
struct scsi_cmnd *cmd = qc->scsicmd;
struct ata_taskfile *tf = &qc->tf;
@@ -600,7 +600,7 @@
* LOCKING:
* inherited from caller
*/
-void ata_gen_fixed_sense(struct ata_queued_cmd *qc)
+static void ata_gen_fixed_sense(struct ata_queued_cmd *qc)
{
struct scsi_cmnd *cmd = qc->scsicmd;
struct ata_taskfile *tf = &qc->tf;
```

—
To unsubscribe from this list: send the line "unsubscribe linux-kernel" in
the body of a message to majordomo@xxxxxxxxxxxxxxxxx
More majordomo info at <http://vger.kernel.org/majordomo-info.html>
Please read the FAQ at <http://www.tux.org/lkml/>

-
- Prev by Date: [\[2.6 patch\] drivers/input/: make some functions static](#)
 - Next by Date: [\[2.6 patch\] ISDN CAPI CAPIFS related cleanups](#)
 - Previous by thread: [\[2.6 patch\] drivers/input/: make some functions static](#)
 - Next by thread: [\[2.6 patch\] ISDN CAPI CAPIFS related cleanups](#)
 - Index(es):
 - ◆ [Date](#)
 - ◆ [Thread](#)