

Re: Which is simpler? (Was Re: [Suspend2-devel] Re: [00/10] [Suspend2] Modules support.)

Re: Which is simpler? (Was Re: [Suspend2-devel] Re: [00/10] [Suspend2] Modules support.)

Source: <http://linux.derkeiler.com/Mailing-Lists/Kernel/2006-02/msg02954.html>

- *From:* "Rafael J. Wysocki" <rjw@xxxxxxx>
 - *Date:* Wed, 8 Feb 2006 15:23:14 +0100
-

Hi,

On Wednesday 08 February 2006 14:23, Bodo Eggert wrote:

There are some questions I have while looking at this HOWTO, which I think should be answered there:

Pavel Machek <pavel@xxxxxx> wrote:

Suspend-to-disk HOWTO

~~~~~

[...]

```
./suspend /dev/<your_swap_partition>
```

Does it need to be mounted (so it possibly gets filled and thereby unusable), or can it be a mkswapped partition?

A mkswapped one will do. Actually a mounted one will do either and the data on it won't get damaged.

Can it even be a swap-file?

No.

Probably not, unless you want to resume by ro-nojournalreplay-mounting the corresponding partition.

How big does it have to be, compared to the RAM? As big + n? Bigger? BIGGER?

Re: Which is simpler? (Was Re: [Suspend2-devel] Re: [ 00/10] [Suspend2] Modules support.)

May be smaller. You'll need at most 1/2 of your RAM size of free space on it.

I'll put the answers in the howto, thanks for the hint.

Greetings,

Rafael

—

To unsubscribe from this list: send the line "unsubscribe linux-kernel" in the body of a message to majordomo@xxxxxxxxxxxxxxxx

More majordomo info at <http://vger.kernel.org/majordomo-info.html>

Please read the FAQ at <http://www.tux.org/lkml/>