

[PATCH 01/13] cell: always build spu base into the kernel

Source: <http://linux.derkeiler.com/Mailing-Lists/Kernel/2006-04/msg06632.html>

- *From:* Arnd Bergmann <arnd@xxxxxxxx>
 - *Date:* Sun, 30 Apr 2006 01:28:13 +0200
-

The spu_base module is rather deeply intermixed with the core kernel, so it makes sense to have that built-in. This will let us extend the base in the future without having to export more core symbols just for it.

Signed-off-by: Arnd Bergmann <arnd.bergmann@xxxxxxxx>

Index: linux-2.6/arch/powerpc/platforms/cell/Makefile

```
=====
--- linux-2.6.orig/arch/powerpc/platforms/cell/Makefile 2006-04-29 22:47:56.000000000 +0200
+++ linux-2.6/arch/powerpc/platforms/cell/Makefile 2006-04-29 22:53:41.000000000 +0200
@@ -2,15 +2,13 @@
obj-y += pervasive.o

obj-$(CONFIG_SMP) += smp.o
-obj-$(CONFIG_SPU_FS) += spu-base.o spufs/
-
-spu-base-y += spu_base.o spu_priv1.o

# needed only when building loadable spufs.ko
spufs-modular-$(CONFIG_SPU_FS) += spu_syscalls.o
obj-y += $(spufs-modular-m)

# always needed in kernel
-spufs-builtin-$(CONFIG_SPU_FS) += spu_callbacks.o
+spufs-builtin-$(CONFIG_SPU_FS) += spu_callbacks.o spu_base.o spu_priv1.o
obj-y += $(spufs-builtin-y) $(spufs-builtin-m)

+obj-$(CONFIG_SPU_FS) += spufs/

---
```

To unsubscribe from this list: send the line "unsubscribe linux-kernel" in the body of a message to majordomo@xxxxxxxxxxxxxxxx
More majordomo info at <http://vger.kernel.org/majordomo-info.html>
Please read the FAQ at <http://www.tux.org/lkml/>