

[BUG] ide-core reports missing symbol init_cmd640_vlb

Source: <http://linux.derkeiler.com/Mailing-Lists/Kernel/2006-05/msg07966.html>

- *From:* Aki Tuomi <cmouse@xxxxxxxxxxxxxxxxxxx>
 - *Date:* Tue, 30 May 2006 09:55:27 +0300
-

I am using debian sarge with following software versions to compile kernel 2.4.32

gcc version 3.3.5 (Debian 1:3.3.5-13)
modutils version 2.4.26

Please find used config file attached.

Result of depmod

```
# depmod -ae -F /boot/System.map-2.4.32 2.4.32
depmod: *** Unresolved symbols in
/lib/modules/2.4.32/kernel/drivers/ide/ide-core.o
depmod: init_cmd640_vlb
```

Kernel compiled using command

```
make-kpkg buildpackage
```

And installed with

```
dpkg -i kernel-image-2.4.32_10.00.Custom_i386.deb
```

```
.....
```

```
/etc/kernel-img.conf
```

```
.....
```

```
do_symlinks = yes
```

```
relative_links = yes
```

```
do_bootloader = no
```

```
do_bootfloppy = no
```

```
do_initrd = yes
```

```
link_in_boot = no
```

```
postinst_hook = /sbin/update-grub
```

```
postrm_hook = /sbin/update-grub
```

```
.....
```

```
/etc/kernel-pkg.conf
```

```
.....
```

```
# This file is used by kernel-package (>2.0) to provide a means of the site
```

```
# admin to over-ride settings in the distributed debian/rules. Typically
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
# thus is used to set maintainer information, as well as the priority
# field. However, one may hack a full makefile in here (you should
# really know what you are doing here if you do that, though)

# Please change the maintainer information, as well as the Debian version
# below, (and maybe the priority as well, especially if you are uploading
# an official package)

# The maintainer information.
maintainer := Aki Tuomi
email := <removed>

# Priority of this version (or urgency, as dchanges would call it)
priority := Low

# This is the Debian revision number (defaulted to 1.0 in debian/rules)
# You may leave it commented out if you use the wrapper script, or
# if you create just one kernel-image package per Linux kernel revision
# debian := 1.0

Aki Tuomi
#
# Automatically generated make config: don't edit
#
CONFIG_X86=y
# CONFIG_SBUS is not set
CONFIG_UID16=y

#
# Code maturity level options
#
CONFIG_EXPERIMENTAL=y

#
# Loadable module support
#
CONFIG_MODULES=y
CONFIG_MODVERSIONS=y
CONFIG_KMOD=y

#
# Processor type and features
#
# CONFIG_M386 is not set
# CONFIG_M486 is not set
CONFIG_M586=y
# CONFIG_M586TSC is not set
# CONFIG_M586MMX is not set
# CONFIG_M686 is not set
# CONFIG_MPENTIUMIII is not set
# CONFIG_MPENTIUM4 is not set
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
# CONFIG_MK6 is not set
# CONFIG_MK7 is not set
# CONFIG_MK8 is not set
# CONFIG_MELAN is not set
# CONFIG_MCRUSOE is not set
# CONFIG_MWINCHIP6 is not set
# CONFIG_MWINCHIP2 is not set
# CONFIG_MWINCHIP3D is not set
# CONFIG_MCYRIXIII is not set
# CONFIG_MVIAC3_2 is not set
CONFIG_X86_WP_WORKS_OK=y
CONFIG_X86_INVLPG=y
CONFIG_X86_CMPXCHG=y
CONFIG_X86_XADD=y
CONFIG_X86_BSWAP=y
CONFIG_X86_POPAD_OK=y
# CONFIG_RWSEM_GENERIC_SPINLOCK is not set
CONFIG_RWSEM_XCHGADD_ALGORITHM=y
CONFIG_X86_L1_CACHE_SHIFT=5
CONFIG_X86_USE_STRING_486=y
CONFIG_X86_ALIGNMENT_16=y
CONFIG_X86_PPRO_FENCE=y
# CONFIG_X86_F00F_WORKS_OK is not set
CONFIG_X86_MCE=y
# CONFIG_TOSHIBA is not set
# CONFIG_I8K is not set
# CONFIG_MICROCODE is not set
# CONFIG_X86_MSR is not set
# CONFIG_X86_CPUID is not set
CONFIG_EDD=m
# CONFIG_NOHIGHMEM is not set
CONFIG_HIGHMEM4G=y
# CONFIG_HIGHMEM64G is not set
CONFIG_HIGHMEM=y
CONFIG_HIGHIO=y
# CONFIG_MATH_EMULATION is not set
CONFIG_MTRR=y
# CONFIG_SMP is not set
CONFIG_X86_UP_APIC=y
CONFIG_X86_UP_IOAPIC=y
CONFIG_X86_LOCAL_APIC=y
CONFIG_X86_IO_APIC=y
# CONFIG_X86_TSC_DISABLE is not set

#
# General setup
#
CONFIG_NET=y
CONFIG_PCI=y
# CONFIG_PCI_GOBIOS is not set
# CONFIG_PCI_GODIRECT is not set
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_PCI_GOANY=y
CONFIG_PCI_BIOS=y
CONFIG_PCI_DIRECT=y
CONFIG_ISA=y
CONFIG_PCI_NAMES=y
CONFIG_EISA=y
CONFIG_MCA=y
CONFIG_HOTPLUG=y

#
# PCMCIA/CardBus support
#
CONFIG_PCMCIA=m
CONFIG_CARDBUS=y
CONFIG_TCIC=y
CONFIG_I82092=y
CONFIG_I82365=y

#
# PCI Hotplug Support
#
CONFIG_HOTPLUG_PCI=m
CONFIG_HOTPLUG_PCI_COMPAQ=m
CONFIG_HOTPLUG_PCI_COMPAQ_NVRAM=y
CONFIG_HOTPLUG_PCI_IBM=m
CONFIG_HOTPLUG_PCI_ACPI=m
CONFIG_HOTPLUG_PCI_SHPC=m
# CONFIG_HOTPLUG_PCI_SHPC_POLL_EVENT_MODE is not set
CONFIG_HOTPLUG_PCI_PCIE=m
# CONFIG_HOTPLUG_PCI_PCIE_POLL_EVENT_MODE is not set
CONFIG_SYSVIPC=y
CONFIG_BSD_PROCESS_ACCT=y
CONFIG_SYSCTL=y
CONFIG_KCORE_ELF=y
# CONFIG_KCORE_AOUT is not set
CONFIG_BINFMT_AOUT=m
CONFIG_BINFMT_ELF=y
CONFIG_BINFMT_MISC=m
# CONFIG_OOM_KILLER is not set
CONFIG_PM=y
CONFIG_APM=m
# CONFIG_APM_IGNORE_USER_SUSPEND is not set
# CONFIG_APM_DO_ENABLE is not set
# CONFIG_APM_CPU_IDLE is not set
# CONFIG_APM_DISPLAY_BLANK is not set
# CONFIG_APM_RTC_IS_GMT is not set
# CONFIG_APM_ALLOW_INTS is not set
# CONFIG_APM_REAL_MODE_POWER_OFF is not set

#
# ACPI Support
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
#
CONFIG_ACPI=y
CONFIG_ACPI_BOOT=y
CONFIG_ACPI_BUS=y
CONFIG_ACPI_INTERPRETER=y
CONFIG_ACPI_EC=y
CONFIG_ACPI_POWER=y
CONFIG_ACPI_PCI=y
CONFIG_ACPI_MMCONFIG=y
CONFIG_ACPI_SLEEP=y
CONFIG_ACPI_SYSTEM=y
CONFIG_ACPI_AC=m
CONFIG_ACPI_BATTERY=m
CONFIG_ACPI_BUTTON=m
CONFIG_ACPI_FAN=m
CONFIG_ACPI_PROCESSOR=m
CONFIG_ACPI_THERMAL=m
CONFIG_ACPI_ASUS=m
CONFIG_ACPI_TOSHIBA=m
# CONFIG_ACPI_DEBUG is not set

#
# Memory Technology Devices (MTD)
#
CONFIG_MTD=m
# CONFIG_MTD_DEBUG is not set
CONFIG_MTD_PARTITIONS=m
CONFIG_MTD_CONCAT=m
CONFIG_MTD_REDBOOT_PARTS=m
CONFIG_MTD_CMDLINE_PARTS=m

#
# User Modules And Translation Layers
#
CONFIG_MTD_CHAR=m
CONFIG_MTD_BLOCK=m
CONFIG_MTD_BLOCK_RO=m
CONFIG_FTL=m
CONFIG_NFTL=m
CONFIG_NFTL_RW=y

#
# RAM/ROM/Flash chip drivers
#
CONFIG_MTD_CFI=m
CONFIG_MTD_JEDECPROBE=m
CONFIG_MTD_GEN_PROBE=m
# CONFIG_MTD_CFI_ADV_OPTIONS is not set
CONFIG_MTD_CFI_INTELEXT=m
CONFIG_MTD_CFI_AMDSTD=m
CONFIG_MTD_CFI_STAA=m
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_MTD_RAM=m
CONFIG_MTD_ROM=m
CONFIG_MTD_ABSENT=m
# CONFIG_MTD_OBSOLETE_CHIPS is not set
# CONFIG_MTD_AMDSTD is not set
# CONFIG_MTD_SHARP is not set
# CONFIG_MTD_JEDEC is not set

#
# Mapping drivers for chip access
#
CONFIG_MTD_PHYSMAP=m
CONFIG_MTD_PHYSMAP_START=0x8000000
CONFIG_MTD_PHYSMAP_LEN=0x4000000
CONFIG_MTD_PHYSMAP_BUSWIDTH=2
CONFIG_MTD_PNC2000=m
CONFIG_MTD_SC520CDP=m
CONFIG_MTD_NETSC520=m
CONFIG_MTD_SBC_GXX=m
CONFIG_MTD_ELAN_104NC=m
CONFIG_MTD_DILNETPC=m
CONFIG_MTD_DILNETPC_BOOTSIZE=0x80000
# CONFIG_MTD_MIXMEM is not set
# CONFIG_MTD_OCTAGON is not set
# CONFIG_MTD_VMAX is not set
CONFIG_MTD_SCx200_DOCFLASH=m
# CONFIG_MTD_L440GX is not set
CONFIG_MTD_AMD76XR0M=m
CONFIG_MTD_ICH2ROM=m
CONFIG_MTD_NETtel=m
CONFIG_MTD_SCB2_FLASH=m
CONFIG_MTD_PCI=m
CONFIG_MTD_PCMCIA=m

#
# Self-contained MTD device drivers
#
CONFIG_MTD_PMC551=m
# CONFIG_MTD_PMC551_BUGFIX is not set
# CONFIG_MTD_PMC551_DEBUG is not set
CONFIG_MTD_SLRAM=m
CONFIG_MTD_MTDDRAM=m
CONFIG_MTDDRAM_TOTAL_SIZE=4096
CONFIG_MTDDRAM_ERASE_SIZE=128
CONFIG_MTD_BLKMTD=m

#
# Disk-On-Chip Device Drivers
#
CONFIG_MTD_DOC1000=m
CONFIG_MTD_DOC2000=m
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_MTD_DOC2001=m
CONFIG_MTD_DOCPROBE=m
# CONFIG_MTD_DOCPROBE_ADVANCED is not set
CONFIG_MTD_DOCPROBE_ADDRESS=0
# CONFIG_MTD_DOCPROBE_HIGH is not set
# CONFIG_MTD_DOCPROBE_55AA is not set
```

```
#
# NAND Flash Device Drivers
#
CONFIG_MTD_NAND=m
# CONFIG_MTD_NAND_VERIFY_WRITE is not set
CONFIG_MTD_NAND_IDS=m
```

```
#
# Parallel port support
#
CONFIG_PARPORT=m
CONFIG_PARPORT_PC=m
CONFIG_PARPORT_PC_CML1=m
CONFIG_PARPORT_SERIAL=m
CONFIG_PARPORT_PC_FIFO=y
# CONFIG_PARPORT_PC_SUPERIO is not set
CONFIG_PARPORT_PC_PCMCIA=m
# CONFIG_PARPORT_AMIGA is not set
# CONFIG_PARPORT_MFC3 is not set
# CONFIG_PARPORT_ATARI is not set
# CONFIG_PARPORT_GSC is not set
# CONFIG_PARPORT_SUNBPP is not set
# CONFIG_PARPORT_IP22 is not set
# CONFIG_PARPORT_OTHER is not set
CONFIG_PARPORT_1284=y
```

```
#
# Plug and Play configuration
#
CONFIG_PNP=m
CONFIG_ISAPNP=m
```

```
#
# Block devices
#
CONFIG_BLK_DEV_FD=m
CONFIG_BLK_DEV_PS2=m
CONFIG_BLK_DEV_XD=m
CONFIG_PARIDE=m
CONFIG_PARIDE_PARPORT=m
```

```
#
# Parallel IDE high-level drivers
#
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_PARIDE_PD=m
CONFIG_PARIDE_PCD=m
CONFIG_PARIDE_PF=m
CONFIG_PARIDE_PT=m
CONFIG_PARIDE_PG=m

#
# Parallel IDE protocol modules
#
CONFIG_PARIDE_ATEN=m
CONFIG_PARIDE_BPCK=m
CONFIG_PARIDE_BPCK6=m
CONFIG_PARIDE_COMM=m
CONFIG_PARIDE_DSTR=m
CONFIG_PARIDE_FIT2=m
CONFIG_PARIDE_FIT3=m
CONFIG_PARIDE_EPAT=m
# CONFIG_PARIDE_EPATC8 is not set
CONFIG_PARIDE_EPIA=m
CONFIG_PARIDE_FRIQ=m
CONFIG_PARIDE_FRPW=m
CONFIG_PARIDE_KBIC=m
CONFIG_PARIDE_KTTI=m
CONFIG_PARIDE_ON20=m
CONFIG_PARIDE_ON26=m
CONFIG_BLK_CPQ_DA=m
CONFIG_BLK_CPQ_CISS_DA=m
CONFIG_CISS_SCSI_TAPE=y
CONFIG_CISS_MONITOR_THREAD=y
CONFIG_BLK_DEV_DAC960=m
CONFIG_BLK_DEV_UMEM=m
CONFIG_BLK_DEV_SX8=m
CONFIG_BLK_DEV_LOOP=m
CONFIG_BLK_DEV_NBD=m
CONFIG_BLK_DEV_RAM=y
CONFIG_BLK_DEV_RAM_SIZE=8192
CONFIG_BLK_DEV_INITRD=y
CONFIG_BLK_STATS=y

#
# Multi-device support (RAID and LVM)
#
CONFIG_MD=y
CONFIG_BLK_DEV_MD=m
CONFIG_MD_LINEAR=m
CONFIG_MD_RAID0=m
CONFIG_MD_RAID1=m
CONFIG_MD_RAID5=m
CONFIG_MD_MULTIPATH=m
CONFIG_BLK_DEV_LVM=m
```

```
#
# Networking options
#
CONFIG_PACKET=m
CONFIG_PACKET_MMAP=y
CONFIG_NETLINK_DEV=m
CONFIG_NETFILTER=y
# CONFIG_NETFILTER_DEBUG is not set
CONFIG_FILTER=y
CONFIG_UNIX=m
CONFIG_INET=y
CONFIG_IP_MULTICAST=y
CONFIG_IP_ADVANCED_ROUTER=y
CONFIG_IP_MULTIPLE_TABLES=y
CONFIG_IP_ROUTE_FWMARK=y
CONFIG_IP_ROUTE_NAT=y
CONFIG_IP_ROUTE_MULTIPATH=y
CONFIG_IP_ROUTE_TOS=y
CONFIG_IP_ROUTE_VERBOSE=y
# CONFIG_IP_PNP is not set
CONFIG_NET_IPIP=m
CONFIG_NET_IPGRE=m
CONFIG_NET_IPGRE_BROADCAST=y
CONFIG_IP_MROUTE=y
CONFIG_IP_PIMSM_V1=y
CONFIG_IP_PIMSM_V2=y
# CONFIG_ARPD is not set
# CONFIG_INET_ECN is not set
CONFIG_SYN_COOKIES=y

#
# IP: Netfilter Configuration
#
CONFIG_IP_NF_CONNTRACK=m
CONFIG_IP_NF_FTP=m
CONFIG_IP_NF_AMANDA=m
CONFIG_IP_NF_TFTP=m
CONFIG_IP_NF_IRC=m
CONFIG_IP_NF_QUEUE=m
CONFIG_IP_NF_IPTABLES=m
CONFIG_IP_NF_MATCH_LIMIT=m
CONFIG_IP_NF_MATCH_MAC=m
CONFIG_IP_NF_MATCH_PKTTYPE=m
CONFIG_IP_NF_MATCH_MARK=m
CONFIG_IP_NF_MATCH_MULTIPORT=m
CONFIG_IP_NF_MATCH_TOS=m
CONFIG_IP_NF_MATCH_RECENT=m
CONFIG_IP_NF_MATCH_ECN=m
CONFIG_IP_NF_MATCH_DSCP=m
CONFIG_IP_NF_MATCH_AH_ESP=m
CONFIG_IP_NF_MATCH_LENGTH=m
```

```
CONFIG_IP_NF_MATCH_TTL=m
CONFIG_IP_NF_MATCH_TCPMSS=m
CONFIG_IP_NF_MATCH_HELPER=m
CONFIG_IP_NF_MATCH_STATE=m
CONFIG_IP_NF_MATCH_CONNTRACK=m
CONFIG_IP_NF_MATCH_UNCLEAN=m
CONFIG_IP_NF_MATCH_OWNER=m
CONFIG_IP_NF_FILTER=m
CONFIG_IP_NF_TARGET_REJECT=m
CONFIG_IP_NF_TARGET_MIRROR=m
CONFIG_IP_NF_NAT=m
CONFIG_IP_NF_NAT_NEEDED=y
CONFIG_IP_NF_TARGET_MASQUERADE=m
CONFIG_IP_NF_TARGET_REDIRECT=m
CONFIG_IP_NF_NAT_AMANDA=m
CONFIG_IP_NF_NAT_SNMP_BASIC=m
CONFIG_IP_NF_NAT_IRC=m
CONFIG_IP_NF_NAT_FTP=m
CONFIG_IP_NF_NAT_TFTP=m
CONFIG_IP_NF_MANGLE=m
CONFIG_IP_NF_TARGET_TOS=m
CONFIG_IP_NF_TARGET_ECN=m
CONFIG_IP_NF_TARGET_DSCP=m
CONFIG_IP_NF_TARGET_MARK=m
CONFIG_IP_NF_TARGET_LOG=m
CONFIG_IP_NF_TARGET_ULOG=m
CONFIG_IP_NF_TARGET_TCPMSS=m
CONFIG_IP_NF_ARPTABLES=m
CONFIG_IP_NF_ARPFILTER=m
CONFIG_IP_NF_ARP_MANGLE=m
CONFIG_IP_NF_COMPAT_IPCHAINS=m
CONFIG_IP_NF_NAT_NEEDED=y
CONFIG_IP_NF_COMPAT_IPFWADM=m
CONFIG_IP_NF_NAT_NEEDED=y
```

```
#
# IP: Virtual Server Configuration
#
CONFIG_IP_VS=m
# CONFIG_IP_VS_DEBUG is not set
CONFIG_IP_VS_TAB_BITS=12
```

```
#
# IPVS scheduler
#
CONFIG_IP_VS_RR=m
CONFIG_IP_VS_WRR=m
CONFIG_IP_VS_LC=m
CONFIG_IP_VS_WLC=m
CONFIG_IP_VS_LBLC=m
CONFIG_IP_VS_LBLCR=m
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_IP_VS_DH=m
CONFIG_IP_VS_SH=m
CONFIG_IP_VS_SED=m
CONFIG_IP_VS_NQ=m

#
# IPVS application helper
#
CONFIG_IP_VS_FTP=m
CONFIG_IPV6=m

#
# IPv6: Netfilter Configuration
#
CONFIG_IP6_NF_QUEUE=m
CONFIG_IP6_NF_IPTABLES=m
CONFIG_IP6_NF_MATCH_LIMIT=m
CONFIG_IP6_NF_MATCH_MAC=m
CONFIG_IP6_NF_MATCH_RT=m
CONFIG_IP6_NF_MATCH_OPTS=m
CONFIG_IP6_NF_MATCH_FRAG=m
CONFIG_IP6_NF_MATCH_HL=m
CONFIG_IP6_NF_MATCH_MULTIPORT=m
CONFIG_IP6_NF_MATCH_OWNER=m
CONFIG_IP6_NF_MATCH_MARK=m
CONFIG_IP6_NF_MATCH_IPV6HEADER=m
CONFIG_IP6_NF_MATCH_AHESP=m
CONFIG_IP6_NF_MATCH_LENGTH=m
CONFIG_IP6_NF_MATCH_EUI64=m
CONFIG_IP6_NF_FILTER=m
CONFIG_IP6_NF_TARGET_LOG=m
CONFIG_IP6_NF_MANGLE=m
CONFIG_IP6_NF_TARGET_MARK=m
CONFIG_KHTTPD=m

#
# SCTP Configuration (EXPERIMENTAL)
#
CONFIG_IP_SCTP=m
# CONFIG_SCTP_DBG_MSG is not set
# CONFIG_SCTP_DBG_OBJCNT is not set
# CONFIG_SCTP_HMAC_NONE is not set
# CONFIG_SCTP_HMAC_SHA1 is not set
CONFIG_SCTP_HMAC_MD5=y
CONFIG_ATM=y
CONFIG_ATM_CLIP=y
# CONFIG_ATM_CLIP_NO_ICMP is not set
CONFIG_ATM_LANE=m
CONFIG_ATM_MPOA=m
CONFIG_ATM_BR2684=m
# CONFIG_ATM_BR2684_IPFILTER is not set
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_VLAN_8021Q=m

#
#
#
CONFIG_IPX=m
# CONFIG_IPX_INTERN is not set
CONFIG_ATALK=m

#
# Appletalk devices
#
CONFIG_DEV_APPLETALK=y
CONFIG_LTPC=m
CONFIG_COPS=m
CONFIG_COPS_DAYNA=y
CONFIG_COPS_TANGENT=y
CONFIG_IPDDP=m
CONFIG_IPDDP_ENCAP=y
CONFIG_IPDDP_DECAP=y
CONFIG_DECNET=m
# CONFIG_DECNET_SIOCGIFCONF is not set
CONFIG_DECNET_ROUTER=y
CONFIG_DECNET_ROUTE_FWMARK=y
CONFIG_BRIDGE=m
CONFIG_X25=m
CONFIG_LAPB=m
# CONFIG_LLC is not set
# CONFIG_NET_DIVERT is not set
CONFIG_ECONET=m
CONFIG_ECONET_AUNUDP=y
CONFIG_ECONET_NATIVE=y
CONFIG_WAN_ROUTER=m
# CONFIG_NET_FASTROUTE is not set
# CONFIG_NET_HW_FLOWCONTROL is not set

#
# QoS and/or fair queueing
#
CONFIG_NET_SCHED=y
CONFIG_NET_SCH_CBQ=m
CONFIG_NET_SCH_HTB=m
CONFIG_NET_SCH_CSZ=m
CONFIG_NET_SCH_HFSC=m
# CONFIG_NET_SCH_ATM is not set
CONFIG_NET_SCH_PRIO=m
CONFIG_NET_SCH_RED=m
CONFIG_NET_SCH_SFQ=m
CONFIG_NET_SCH_TEQL=m
CONFIG_NET_SCH_TBF=m
CONFIG_NET_SCH_GRED=m
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_NET_SCH_NETEM=m
CONFIG_NET_SCH_DSMARK=m
CONFIG_NET_SCH_INGRESS=m
CONFIG_NET_QOS=y
CONFIG_NET_ESTIMATOR=y
CONFIG_NET_CLS=y
CONFIG_NET_CLS_TCINDEX=m
CONFIG_NET_CLS_ROUTE4=m
CONFIG_NET_CLS_ROUTE=y
CONFIG_NET_CLS_FW=m
CONFIG_NET_CLS_U32=m
CONFIG_NET_CLS_RSVP=m
CONFIG_NET_CLS_RSVP6=m
CONFIG_NET_CLS_POLICE=y

#
# Network testing
#
CONFIG_NET_PKTGEN=m

#
# Telephony Support
#
CONFIG_PHONE=m
CONFIG_PHONE_IXJ=m
CONFIG_PHONE_IXJ_PCMCIA=m

#
# ATA/IDE/MFM/RLL support
#
CONFIG_IDE=m

#
# IDE, ATA and ATAPI Block devices
#
CONFIG_BLK_DEV_IDE=m

#
# Please see Documentation/ide.txt for help/info on IDE drives
#
# CONFIG_BLK_DEV_HD_IDE is not set
# CONFIG_BLK_DEV_HD is not set
# CONFIG_BLK_DEV_IDE_SATA is not set
CONFIG_BLK_DEV_IDEDISK=m
CONFIG_IDEDISK_MULTI_MODE=y
# CONFIG_IDEDISK_STROKE is not set
CONFIG_BLK_DEV_IDECS=m
CONFIG_BLK_DEV_DELKIN=m
CONFIG_BLK_DEV_IDECD=m
CONFIG_BLK_DEV_IDETAPE=m
CONFIG_BLK_DEV_IDEFLOPPY=m
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_BLK_DEV_IDESCSI=m
# CONFIG_IDE_TASK_IOCTL is not set

#
# IDE chipset support/bugfixes
#
CONFIG_BLK_DEV_CMD640=y
CONFIG_BLK_DEV_CMD640_ENHANCED=y
# CONFIG_BLK_DEV_ISAPNP is not set
CONFIG_BLK_DEV_IDEPCI=y
CONFIG_BLK_DEV_GENERIC=y
CONFIG_IDEPCI_SHARE_IRQ=y
CONFIG_BLK_DEV_IDEDMA_PCI=y
# CONFIG_BLK_DEV_OFFBOARD is not set
# CONFIG_BLK_DEV_IDEDMA_FORCED is not set
CONFIG_IDEDMA_PCI_AUTO=y
# CONFIG_IDEDMA_ONLYDISK is not set
CONFIG_BLK_DEV_IDEDMA=y
# CONFIG_IDEDMA_PCI_WIP is not set
CONFIG_BLK_DEV_ADMA100=m
CONFIG_BLK_DEV_AEC62XX=m
CONFIG_BLK_DEV_ALI15X3=m
# CONFIG_WDC_ALI15X3 is not set
CONFIG_BLK_DEV_AMD74XX=m
# CONFIG_AMD74XX_OVERRIDE is not set
CONFIG_BLK_DEV_ATIIXP=m
CONFIG_BLK_DEV_CMD64X=y
CONFIG_BLK_DEV_TRIFLEX=m
CONFIG_BLK_DEV_CY82C693=m
CONFIG_BLK_DEV_CS5530=m
CONFIG_BLK_DEV_HPT34X=m
# CONFIG_HPT34X_AUTODMA is not set
CONFIG_BLK_DEV_HPT366=m
CONFIG_BLK_DEV_PIIX=m
CONFIG_BLK_DEV_NS87415=m
CONFIG_BLK_DEV_OPTI621=m
CONFIG_BLK_DEV_PDC202XX_OLD=m
CONFIG_PDC202XX_BURST=y
CONFIG_BLK_DEV_PDC202XX_NEW=m
CONFIG_PDC202XX_FORCE=y
CONFIG_BLK_DEV_RZ1000=m
CONFIG_BLK_DEV_SC1200=m
CONFIG_BLK_DEV_SVWKS=y
CONFIG_BLK_DEV_SIIMAGE=m
CONFIG_BLK_DEV_SIS5513=m
CONFIG_BLK_DEV_SLC90E66=m
CONFIG_BLK_DEV_TRM290=m
CONFIG_BLK_DEV_VIA82CXXX=m
# CONFIG_IDE_CHIPSETS is not set
CONFIG_IDEDMA_AUTO=y
# CONFIG_IDEDMA_IVB is not set
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
# CONFIG_DMA_NONPCI is not set
CONFIG_BLK_DEV_PDC202XX=y
CONFIG_BLK_DEV_ATA RAID=m
CONFIG_BLK_DEV_ATA RAID_PDC=m
CONFIG_BLK_DEV_ATA RAID_HPT=m
CONFIG_BLK_DEV_ATA RAID_MEDLEY=m
CONFIG_BLK_DEV_ATA RAID_SII=m

#
# SCSI support
#
CONFIG_SCSI=m

#
# SCSI support type (disk, tape, CD-ROM)
#
CONFIG_BLK_DEV_SD=m
CONFIG_SD_EXTRA_DEVS=40
CONFIG_CHR_DEV_ST=m
CONFIG_CHR_DEV_OSST=m
CONFIG_BLK_DEV_SR=m
# CONFIG_BLK_DEV_SR_VENDOR is not set
CONFIG_SR_EXTRA_DEVS=2
CONFIG_CHR_DEV_SG=m

#
# Some SCSI devices (e.g. CD jukebox) support multiple LUNs
#
# CONFIG_SCSI_DEBUG_QUEUES is not set
CONFIG_SCSI_MULTI_LUN=y
CONFIG_SCSI_CONSTANTS=y
CONFIG_SCSI_LOGGING=y

#
# SCSI low-level drivers
#
CONFIG_BLK_DEV_3W_XXXX_RAID=m
CONFIG_SCSI_7000FASST=m
CONFIG_SCSI_ACARD=m
CONFIG_SCSI_AHA152X=m
CONFIG_SCSI_AHA1542=m
CONFIG_SCSI_AHA1740=m
CONFIG_SCSI_AACRAID=m
CONFIG_SCSI_AIC7XXX=m
CONFIG_AIC7XXX_CMDS_PER_DEVICE=8
CONFIG_AIC7XXX_RESET_DELAY_MS=15000
CONFIG_AIC7XXX_PROBE_EISA_VL=y
# CONFIG_AIC7XXX_BUILD_FIRMWARE is not set
# CONFIG_AIC7XXX_DEBUG_ENABLE is not set
CONFIG_AIC7XXX_DEBUG_MASK=0
# CONFIG_AIC7XXX_REG_PRETTY_PRINT is not set
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_SCSI_AIC79XX=m
CONFIG_AIC79XX_CMDS_PER_DEVICE=32
CONFIG_AIC79XX_RESET_DELAY_MS=15000
# CONFIG_AIC79XX_BUILD_FIRMWARE is not set
# CONFIG_AIC79XX_ENABLE_RD_STRM is not set
# CONFIG_AIC79XX_DEBUG_ENABLE is not set
CONFIG_AIC79XX_DEBUG_MASK=0
# CONFIG_AIC79XX_REG_PRETTY_PRINT is not set
CONFIG_SCSI_AIC7XXX_OLD=m
# CONFIG_AIC7XXX_OLD_TCQ_ON_BY_DEFAULT is not set
CONFIG_AIC7XXX_OLD_CMDS_PER_DEVICE=8
CONFIG_AIC7XXX_OLD_PROC_STATS=y
CONFIG_SCSI_DPT_I2O=m
CONFIG_SCSI_ADVANSYS=m
CONFIG_SCSI_IN2000=m
CONFIG_SCSI_AM53C974=m
CONFIG_SCSI_MEGARAID=m
CONFIG_SCSI_MEGARAID2=m
CONFIG_SCSI_SATA=y
CONFIG_SCSI_SATA_AHCI=m
CONFIG_SCSI_SATA_SVW=m
CONFIG_SCSI_ATA_PIIX=m
CONFIG_SCSI_SATA_NV=m
CONFIG_SCSI_SATA_QSTOR=m
CONFIG_SCSI_SATA_PROMISE=m
CONFIG_SCSI_SATA_SX4=m
CONFIG_SCSI_SATA_SIL=m
CONFIG_SCSI_SATA_SIS=m
CONFIG_SCSI_SATA_ULI=m
CONFIG_SCSI_SATA_VIA=m
CONFIG_SCSI_SATA_VITESSE=m
CONFIG_SCSI_BUSLOGIC=m
# CONFIG_SCSI_OMIT_FLASHPOINT is not set
CONFIG_SCSI_CPQFCTS=m
CONFIG_SCSI_DMX3191D=m
CONFIG_SCSI_DTC3280=m
CONFIG_SCSI_EATA=m
# CONFIG_SCSI_EATA_TAGGED_QUEUE is not set
# CONFIG_SCSI_EATA_LINKED_COMMANDS is not set
CONFIG_SCSI_EATA_MAX_TAGS=16
# CONFIG_SCSI_EATA_DMA is not set
CONFIG_SCSI_EATA_PIO=m
CONFIG_SCSI_FUTURE_DOMAIN=m
CONFIG_SCSI_FD_MCS=m
CONFIG_SCSI_GDTH=m
CONFIG_SCSI_GENERIC_NCR5380=m
CONFIG_SCSI_GENERIC_NCR53C400=y
CONFIG_SCSI_G_NCR5380_PORT=y
# CONFIG_SCSI_G_NCR5380_MEM is not set
CONFIG_SCSI_IBMMCA=m
CONFIG_IBMMCA_SCSI_ORDER_STANDARD=y
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
# CONFIG_IBMMCA_SCSI_DEV_RESET is not set
CONFIG_SCSI_IPS=m
CONFIG_SCSI_INITIO=m
CONFIG_SCSI_INIA100=m
CONFIG_SCSI_PPA=m
CONFIG_SCSI_IMM=m
# CONFIG_SCSI_IZIP_EPP16 is not set
# CONFIG_SCSI_IZIP_SLOW_CTR is not set
CONFIG_SCSI_NCR53C406A=m
CONFIG_SCSI_NCR_D700=m
CONFIG_53C700_IO_MAPPED=y
# CONFIG_SCSI_NCR53C7xx is not set
CONFIG_SCSI_SYM53C8XX_2=m
CONFIG_SCSI_SYM53C8XX_DMA_ADDRESSING_MODE=1
CONFIG_SCSI_SYM53C8XX_DEFAULT_TAGS=16
CONFIG_SCSI_SYM53C8XX_MAX_TAGS=64
# CONFIG_SCSI_SYM53C8XX_IOMAPPED is not set
CONFIG_SCSI_NCR53C8XX=m
CONFIG_SCSI_SYM53C8XX=m
CONFIG_SCSI_NCR53C8XX_DEFAULT_TAGS=8
CONFIG_SCSI_NCR53C8XX_MAX_TAGS=4
CONFIG_SCSI_NCR53C8XX_SYNC=5
# CONFIG_SCSI_NCR53C8XX_PROFILE is not set
# CONFIG_SCSI_NCR53C8XX_IOMAPPED is not set
CONFIG_SCSI_NCR53C8XX_PQS_PDS=y
# CONFIG_SCSI_NCR53C8XX_SYMBIOS_COMPAT is not set
CONFIG_SCSI_MCA_53C9X=m
CONFIG_SCSI_PAS16=m
CONFIG_SCSI_PCI2000=m
CONFIG_SCSI_PCI2220I=m
CONFIG_SCSI_PSI240I=m
CONFIG_SCSI_QLOGIC_FAS=m
CONFIG_SCSI_QLOGIC_ISP=m
CONFIG_SCSI_QLOGIC_FC=m
CONFIG_SCSI_QLOGIC_FC_FIRMWARE=y
CONFIG_SCSI_QLOGIC_1280=m
CONFIG_SCSI_SEAGATE=m
CONFIG_SCSI_SIM710=m
CONFIG_SCSI_SYM53C416=m
CONFIG_SCSI_DC390T=m
# CONFIG_SCSI_DC390T_NOGENSUPP is not set
CONFIG_SCSI_T128=m
CONFIG_SCSI_U14_34F=m
# CONFIG_SCSI_U14_34F_LINKED_COMMANDS is not set
CONFIG_SCSI_U14_34F_MAX_TAGS=8
CONFIG_SCSI_ULTRASTOR=m
CONFIG_SCSI_NSP32=m
CONFIG_SCSI_DEBUG=m

#
# PCMCIA SCSI adapter support
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
#
CONFIG_SCSI_PCMCIA=y
CONFIG_PCMCIA_AHA152X=m
CONFIG_PCMCIA_FDOMAIN=m
CONFIG_PCMCIA_NINJA_SCSI=m
CONFIG_PCMCIA_QLOGIC=m

#
# Fusion MPT device support
#
CONFIG_FUSION=m
# CONFIG_FUSION_BOOT is not set
CONFIG_FUSION_MAX_SGE=40
CONFIG_FUSION_ISENSE=m
CONFIG_FUSION_CTL=m
CONFIG_FUSION_LAN=m
CONFIG_NET_FC=y

#
# IEEE 1394 (FireWire) support (EXPERIMENTAL)
#
CONFIG_IEEE1394=m

#
# Device Drivers
#
CONFIG_IEEE1394_PCILYNX=m
CONFIG_IEEE1394_OHCI1394=m

#
# Protocol Drivers
#
CONFIG_IEEE1394_VIDEO1394=m
CONFIG_IEEE1394_SBP2=m
# CONFIG_IEEE1394_SBP2_PHYS_DMA is not set
CONFIG_IEEE1394_ETH1394=m
CONFIG_IEEE1394_DV1394=m
CONFIG_IEEE1394_RAWIO=m
CONFIG_IEEE1394_CMP=m
CONFIG_IEEE1394_AMDTP=m
# CONFIG_IEEE1394_VERBOSEDEBUG is not set
CONFIG_IEEE1394_OUI_DB=y

#
# I2O device support
#
CONFIG_I2O=m
CONFIG_I2O_PCI=m
CONFIG_I2O_BLOCK=m
CONFIG_I2O_LAN=m
CONFIG_I2O_SCSI=m
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_I2O_PROC=m

#
# Network device support
#
CONFIG_NETDEVICES=y

#
# ARCnet devices
#
CONFIG_ARCNET=m
CONFIG_ARCNET_1201=m
CONFIG_ARCNET_1051=m
CONFIG_ARCNET_RAW=m
CONFIG_ARCNET_COM90xx=m
CONFIG_ARCNET_COM90xxIO=m
CONFIG_ARCNET_RIM_I=m
CONFIG_ARCNET_COM20020=m
CONFIG_ARCNET_COM20020_ISA=m
CONFIG_ARCNET_COM20020_PCI=m
CONFIG_DUMMY=m
CONFIG_BONDING=m
CONFIG_EQUALIZER=m
CONFIG_TUN=m
CONFIG_ETHERTAP=m
CONFIG_NET_SB1000=m

#
# Ethernet (10 or 100Mbit)
#
CONFIG_NET_ETHERNET=y
# CONFIG_SUNLANCE is not set
CONFIG_HAPPYMEAL=m
# CONFIG_SUNBMAC is not set
# CONFIG_SUNQE is not set
# CONFIG_SUNGEM is not set
CONFIG_NET_VENDOR_3COM=y
CONFIG_EL1=m
CONFIG_EL2=m
CONFIG_ELPLUS=m
CONFIG_EL16=m
CONFIG_EL3=m
CONFIG_3C515=m
CONFIG_ELMC=m
CONFIG_ELMC_II=m
CONFIG_VORTEX=m
CONFIG_TYPHOON=m
CONFIG_LANCE=m
CONFIG_NET_VENDOR_SMC=y
CONFIG_WD80x3=m
CONFIG_ULTRAMCA=m
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_ULTRA=m
CONFIG_ULTRA32=m
CONFIG_SMC9194=m
CONFIG_NET_VENDOR_RACAL=y
CONFIG_NI5010=m
CONFIG_NI52=m
CONFIG_NI65=m
CONFIG_AT1700=m
CONFIG_DEPCA=m
CONFIG_HP100=m
CONFIG_NET_ISA=y
CONFIG_E2100=m
CONFIG_EWRK3=m
CONFIG_EEXPRESS=m
CONFIG_EEXPRESS_PRO=m
CONFIG_HPLAN_PLUS=m
CONFIG_HPLAN=m
CONFIG_LP486E=m
CONFIG_ETH16I=m
CONFIG_NE2000=m
CONFIG_SKMC=m
CONFIG_NE2_MCA=m
CONFIG_IBMLANA=m
CONFIG_NET_PCI=y
CONFIG_PCNET32=m
CONFIG_AMD8111_ETH=m
CONFIG_ADAPTEC_STARFIRE=m
CONFIG_AC3200=m
CONFIG_APRICOT=m
CONFIG_B44=m
CONFIG_CS89x0=m
CONFIG_TULIP=m
# CONFIG_TULIP_MWI is not set
# CONFIG_TULIP_MMIO is not set
CONFIG_DE4X5=m
CONFIG_DGRS=m
CONFIG_DM9102=m
CONFIG_EEPRO100=m
# CONFIG_EEPRO100_PIO is not set
CONFIG_E100=m
CONFIG_LNE390=m
CONFIG_FEALNX=m
CONFIG_NATSEMI=m
CONFIG_NE2K_PCI=m
CONFIG_FORCEDETH=m
CONFIG_NE3210=m
CONFIG_ES3210=m
CONFIG_8139CP=m
CONFIG_8139TOO=m
CONFIG_8139TOO_PIO=y
# CONFIG_8139TOO_TUNE_TWISTER is not set
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_8139TOO_8129=y
# CONFIG_8139_OLD_RX_RESET is not set
CONFIG_SIS900=m
CONFIG_EPIC100=m
CONFIG_SUNDANCE=m
# CONFIG_SUNDANCE_MMIO is not set
CONFIG_TLAN=m
CONFIG_VIA_RHINE=m
# CONFIG_VIA_RHINE_MMIO is not set
CONFIG_WINBOND_840=m
CONFIG_NET_POCKET=y
CONFIG_ATP=m
CONFIG_DE600=m
CONFIG_DE620=m

#
# Ethernet (1000 Mbit)
#
CONFIG_ACENIC=m
# CONFIG_ACENIC_OMIT_TIGON_I is not set
CONFIG_DL2K=m
CONFIG_E1000=m
CONFIG_E1000_NAPI=y
# CONFIG_MYRI_SBUS is not set
CONFIG_NS83820=m
CONFIG_HAMACHI=m
CONFIG_YELLOWFIN=m
CONFIG_R8169=m
CONFIG_SK98LIN=m
CONFIG_TIGON3=m
CONFIG_FDDI=y
CONFIG_DEFXX=m
CONFIG_SKFP=m
CONFIG_HIPPI=y
CONFIG_ROADRUNNER=m
# CONFIG_ROADRUNNER_LARGE_RINGS is not set
CONFIG_PLIP=m
CONFIG_PPP=m
CONFIG_PPP_MULTILINK=y
CONFIG_PPP_FILTER=y
CONFIG_PPP_ASYNC=m
CONFIG_PPP_SYNC_TTY=m
CONFIG_PPP_DEFLATE=m
CONFIG_PPP_BSDCOMP=m
CONFIG_PPPOE=m
CONFIG_PPPOATM=m
CONFIG_SLIP=m
CONFIG_SLIP_COMPRESSED=y
CONFIG_SLIP_SMART=y
# CONFIG_SLIP_MODE_SLIP6 is not set
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
#  
# Wireless LAN (non-hamradio)  
#  
CONFIG_NET_RADIO=y  
CONFIG_STRIP=m  
CONFIG_WAVELAN=m  
CONFIG_ARLAN=m  
CONFIG_AIRONET4500=m  
CONFIG_AIRONET4500_NONCS=m  
CONFIG_AIRONET4500_PNP=y  
CONFIG_AIRONET4500_PCI=y  
# CONFIG_AIRONET4500_ISA is not set  
# CONFIG_AIRONET4500_I365 is not set  
CONFIG_AIRONET4500_PROC=m  
CONFIG_AIRO=m  
CONFIG_HERMES=m  
CONFIG_PLX_HERMES=m  
CONFIG_TMD_HERMES=m  
CONFIG_PCI_HERMES=m  
  
#  
# Wireless Pcmcia cards support  
#  
CONFIG_PCMCIA_HERMES=m  
CONFIG_AIRO_CS=m  
CONFIG_PCMCIA_ATMEL=m  
  
#  
# Prism54 PCI/PCMCIA GT/Duette Driver – 802.11(a/b/g)  
#  
CONFIG_PRISM54=m  
CONFIG_FW_LOADER=m  
CONFIG_NET_WIRELESS=y  
  
#  
# Token Ring devices  
#  
CONFIG_TR=y  
CONFIG_IBMTR=m  
CONFIG_IBMOL=m  
CONFIG_IBMLS=m  
CONFIG_3C359=m  
CONFIG_TMS380TR=m  
CONFIG_TMSPCI=m  
CONFIG_TMSISA=m  
CONFIG_ABYSS=m  
CONFIG_MADGEMC=m  
CONFIG_SMCTR=m  
CONFIG_NET_FC=y  
CONFIG_IPHASE5526=m  
CONFIG_RCPCI=m
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_SHAPER=m

#
# Wan interfaces
#
CONFIG_WAN=y
CONFIG_HOSTESS_SV11=m
CONFIG_COSA=m
CONFIG_COMX=y
CONFIG_COMX_HW_COMX=m
CONFIG_COMX_HW_LOCOMX=m
CONFIG_COMX_HW_MIXCOM=m
CONFIG_COMX_HW_MUNICH=m
CONFIG_COMX_PROTO_PPP=m
CONFIG_COMX_PROTO_LAPB=m
CONFIG_COMX_PROTO_FR=m
CONFIG_DSCC4=m
# CONFIG_DSCC4_PCISYNC is not set
# CONFIG_DSCC4_PCI_RST is not set
CONFIG_LANMEDIA=m
CONFIG_ATI_XX20=m
CONFIG_SEALEVEL_4021=m
CONFIG_SYNCLINK_SYNCPPP=m
CONFIG_HDLC=m
CONFIG_HDLC_RAW=y
CONFIG_HDLC_RAW_ETH=y
CONFIG_HDLC_CISCO=y
CONFIG_HDLC_FR=y
CONFIG_HDLC_PPP=y
CONFIG_HDLC_X25=y
CONFIG_PCI200SYN=m
CONFIG_PC300=m
CONFIG_PC300_MLPPP=y
CONFIG_FARSYNC=m
CONFIG_N2=m
CONFIG_C101=m
CONFIG_DLCI=m
CONFIG_DLCI_COUNT=24
CONFIG_DLCI_MAX=8
CONFIG_SDLA=m
CONFIG_WAN_ROUTER_DRIVERS=y
CONFIG_VENDOR_SANGOMA=m
CONFIG_WANPIPE_CHDLC=y
CONFIG_WANPIPE_FR=y
CONFIG_WANPIPE_X25=y
CONFIG_WANPIPE_PPP=y
CONFIG_WANPIPE_MULTPPP=y
CONFIG_CYCLADES_SYNC=m
CONFIG_CYCLOMX_X25=y
CONFIG_LAPBETHER=m
CONFIG_X25_ASY=m
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_SBNI=m
# CONFIG_SBNI_MULTILINE is not set

#
# PCMCIA network device support
#
CONFIG_NET_PCMCIA=y
CONFIG_PCMCIA_3C589=m
CONFIG_PCMCIA_3C574=m
CONFIG_PCMCIA_FMVJ18X=m
CONFIG_PCMCIA_PCNET=m
CONFIG_PCMCIA_AXNET=m
CONFIG_PCMCIA_NMCLAN=m
CONFIG_PCMCIA_SMC91C92=m
CONFIG_PCMCIA_XIRC2PS=m
CONFIG_ARCNET_COM20020_CS=m
CONFIG_PCMCIA_IBMTR=m
CONFIG_PCMCIA_XIRCOM=m
CONFIG_PCMCIA_XIRTULIP=m
CONFIG_NET_PCMCIA_RADIO=y
CONFIG_PCMCIA_RAYCS=m
CONFIG_PCMCIA_NETWAVE=m
CONFIG_PCMCIA_WAVELAN=m
CONFIG_AIRONET4500_CS=m

#
# ATM drivers
#
CONFIG_ATM_TCP=m
CONFIG_ATM_LANAI=m
CONFIG_ATM_ENI=m
# CONFIG_ATM_ENI_DEBUG is not set
# CONFIG_ATM_ENI_TUNE_BURST is not set
CONFIG_ATM_FIRESTREAM=m
CONFIG_ATM_ZATM=m
# CONFIG_ATM_ZATM_DEBUG is not set
# CONFIG_ATM_ZATM_EXACT_TS is not set
CONFIG_ATM_NICSTAR=m
# CONFIG_ATM_NICSTAR_USE_SUNI is not set
# CONFIG_ATM_NICSTAR_USE_IDT77105 is not set
CONFIG_ATM_IDT77252=m
# CONFIG_ATM_IDT77252_DEBUG is not set
# CONFIG_ATM_IDT77252_RCV_ALL is not set
CONFIG_ATM_IDT77252_USE_SUNI=y
CONFIG_ATM_AMBASSADOR=m
# CONFIG_ATM_AMBASSADOR_DEBUG is not set
CONFIG_ATM_HORIZON=m
# CONFIG_ATM_HORIZON_DEBUG is not set
CONFIG_ATM_IA=m
# CONFIG_ATM_IA_DEBUG is not set
CONFIG_ATM_FORE200E_MAYBE=m
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
# CONFIG_ATM_FORE200E_PCA is not set
CONFIG_ATM_HE=m
CONFIG_ATM_HE_USE_SUNI=y
```

```
#
# Amateur Radio support
#
CONFIG_HAMRADIO=y
```

```
#
# Packet Radio protocols
#
CONFIG_AX25=m
# CONFIG_AX25_DAMA_SLAVE is not set
CONFIG_NETROM=m
CONFIG_ROSE=m
```

```
#
# AX.25 network device drivers
#
```

```
#
# AX.25 network device drivers
#
CONFIG_MKISS=m
CONFIG_6PACK=m
CONFIG_BPQETHER=m
CONFIG_DMASCC=m
CONFIG_SCC=m
# CONFIG_SCC_DELAY is not set
# CONFIG_SCC_TRXECHO is not set
CONFIG_BAYCOM_SER_FDX=m
CONFIG_BAYCOM_SER_HDX=m
CONFIG_BAYCOM_PAR=m
CONFIG_BAYCOM_EPP=m
CONFIG_SOUNDMODEM=m
CONFIG_SOUNDMODEM_SBC=y
CONFIG_SOUNDMODEM_WSS=y
CONFIG_SOUNDMODEM_AFSK1200=y
CONFIG_SOUNDMODEM_AFSK2400_7=y
CONFIG_SOUNDMODEM_AFSK2400_8=y
CONFIG_SOUNDMODEM_AFSK2666=y
CONFIG_SOUNDMODEM_HAPN4800=y
CONFIG_SOUNDMODEM_PSK4800=y
CONFIG_SOUNDMODEM_FSK9600=y
CONFIG_YAM=m
```

```
#
# IrDA (infrared) support
#
CONFIG_IRDA=m
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
#  
# IrDA protocols  
#  
CONFIG_IRLAN=m  
CONFIG_IRNET=m  
CONFIG_IRCOMM=m  
# CONFIG_IRDA_ULTRA is not set  
  
#  
# IrDA options  
#  
CONFIG_IRDA_CACHE_LAST_LSAP=y  
CONFIG_IRDA_FAST_RR=y  
CONFIG_IRDA_DEBUG=y  
  
#  
# Infrared-port device drivers  
#  
  
#  
# SIR device drivers  
#  
CONFIG_IRTTY_SIR=m  
CONFIG_IRPORT_SIR=m  
  
#  
# Dongle support  
#  
CONFIG_DONGLE=y  
CONFIG_ESI_DONGLE=m  
CONFIG_ACTISYS_DONGLE=m  
CONFIG_TEKRAM_DONGLE=m  
CONFIG_GIRBIL_DONGLE=m  
CONFIG_LITELINK_DONGLE=m  
CONFIG_MCP2120_DONGLE=m  
CONFIG_OLD_BELKIN_DONGLE=m  
CONFIG_ACT200L_DONGLE=m  
CONFIG_MA600_DONGLE=m  
  
#  
# FIR device drivers  
#  
CONFIG_USB_IRDA=m  
CONFIG_NSC_FIR=m  
CONFIG_WINBOND_FIR=m  
CONFIG_TOSHIBA_OLD=m  
CONFIG_TOSHIBA_FIR=m  
CONFIG_SMC_IRCC_FIR=m  
CONFIG_ALI_FIR=m  
CONFIG_VLSI_FIR=m
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_VIA_IRCC_FIR=m

#
# ISDN subsystem
#
CONFIG_ISDN=m
CONFIG_ISDN_BOOL=y
CONFIG_ISDN_PPP=y
CONFIG_IPPP_FILTER=y
CONFIG_ISDN_PPP_VJ=y
CONFIG_ISDN_MPP=y
CONFIG_ISDN_PPP_BSDCOMP=m
CONFIG_ISDN_AUDIO=y
CONFIG_ISDN_TTY_FAX=y
CONFIG_ISDN_X25=y

#
# ISDN feature submodules
#
CONFIG_ISDN_DRV_LOOP=m
CONFIG_ISDN_DIVERSION=m

#
# low-level hardware drivers
#

#
# Passive ISDN cards
#
CONFIG_ISDN_DRV_HISAX=m
CONFIG_ISDN_HISAX=y

#
# D-channel protocol features
#
CONFIG_HISAX_EURO=y
CONFIG_DE_AOC=y
# CONFIG_HISAX_NO_SENDCOMPLETE is not set
# CONFIG_HISAX_NO_LLC is not set
# CONFIG_HISAX_NO_KEYPAD is not set
CONFIG_HISAX_1TR6=y
CONFIG_HISAX_NI1=y
CONFIG_HISAX_MAX_CARDS=8

#
# HiSax supported cards
#
CONFIG_HISAX_16_0=y
CONFIG_HISAX_16_3=y
CONFIG_HISAX_AVM_A1=y
CONFIG_HISAX_IX1MICROR2=y
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_HISAX_ASUSCOM=y
CONFIG_HISAX_TELEINT=y
CONFIG_HISAX_HFCS=y
CONFIG_HISAX_SPORTSTER=y
CONFIG_HISAX_MIC=y
CONFIG_HISAX_ISURF=y
CONFIG_HISAX_HSTSAPHIR=y
CONFIG_HISAX_TELESPCI=y
CONFIG_HISAX_S0BOX=y
CONFIG_HISAX_FRITZPCI=y
CONFIG_HISAX_AVM_A1_PCMCIA=y
CONFIG_HISAX_ELSA=y
CONFIG_HISAX_DIEHLDIVA=y
CONFIG_HISAX_SEDLBAUER=y
CONFIG_HISAX_NETJET=y
CONFIG_HISAX_NETJET_U=y
CONFIG_HISAX_NICCY=y
CONFIG_HISAX_BKM_A4T=y
CONFIG_HISAX_SCT_QUADRO=y
CONFIG_HISAX_GAZEL=y
CONFIG_HISAX_HFC_PCI=y
CONFIG_HISAX_W6692=y
CONFIG_HISAX_HFC_SX=y
CONFIG_HISAX_ENTERNOW_PCI=y
# CONFIG_HISAX_DEBUG is not set
CONFIG_HISAX_SEDLBAUER_CS=m
CONFIG_HISAX_ELSA_CS=m
CONFIG_HISAX_AVM_A1_CS=m
CONFIG_HISAX_ST5481=m
CONFIG_HISAX_FRITZ_PCIPNP=m
CONFIG_USB_AUERISDN=m
```

```
#
# Active ISDN cards
#
CONFIG_ISDN_DRV_ICN=m
CONFIG_ISDN_DRV_PCBIT=m
CONFIG_ISDN_DRV_SC=m
CONFIG_ISDN_DRV_ACT2000=m
CONFIG_ISDN_DRV_EICON=y
CONFIG_ISDN_DRV_EICON_DIVAS=m
CONFIG_ISDN_DRV_EICON_OLD=m
CONFIG_ISDN_DRV_EICON_PCI=y
CONFIG_ISDN_DRV_EICON_ISA=y
CONFIG_ISDN_DRV_TPAM=m
CONFIG_ISDN_CAPI=m
CONFIG_ISDN_DRV_AVMB1_VERBOSE_REASON=y
CONFIG_ISDN_CAPI_MIDDLEWARE=y
CONFIG_ISDN_CAPI_CAPI20=m
CONFIG_ISDN_CAPI_CAPIFS_BOOL=y
CONFIG_ISDN_CAPI_CAPIFS=m
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_ISDN_CAPI_CAPIDRV=m
CONFIG_ISDN_DRV_AVMB1_B1ISA=m
CONFIG_ISDN_DRV_AVMB1_B1PCI=m
CONFIG_ISDN_DRV_AVMB1_B1PCIV4=y
CONFIG_ISDN_DRV_AVMB1_T1ISA=m
CONFIG_ISDN_DRV_AVMB1_B1PCMCIA=m
CONFIG_ISDN_DRV_AVMB1_AVM_CS=m
CONFIG_ISDN_DRV_AVMB1_T1PCI=m
CONFIG_ISDN_DRV_AVMB1_C4=m
CONFIG_HYSDN=m
CONFIG_HYSDN_CAPI=y

#
# Old CD-ROM drivers (not SCSI, not IDE)
#
CONFIG_CD_NO_IDESCSI=y
CONFIG_AZTCD=m
CONFIG_GSCD=m
CONFIG_SBPCD=m
CONFIG_MCD=m
CONFIG_MCD_IRQ=11
CONFIG_MCD_BASE=0x300
CONFIG_MCDX=m
CONFIG_OPTCD=m
CONFIG_CM206=m
CONFIG_SJCD=m
CONFIG_ISP16_CDI=m
CONFIG_CDU31A=m
CONFIG_CDU535=m

#
# Input core support
#
CONFIG_INPUT=m
CONFIG_INPUT_KEYBDEV=m
CONFIG_INPUT_MOUSEDEV=m
CONFIG_INPUT_MOUSEDEV_SCREEN_X=1024
CONFIG_INPUT_MOUSEDEV_SCREEN_Y=768
CONFIG_INPUT_JOYDEV=m
CONFIG_INPUT_EVDEV=m
CONFIG_INPUT_UINPUT=m

#
# Character devices
#
CONFIG_VT=y
CONFIG_VT_CONSOLE=y
CONFIG_SERIAL=y
CONFIG_SERIAL_CONSOLE=y
CONFIG_SERIAL_EXTENDED=y
CONFIG_SERIAL_MANY_PORTS=y
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_SERIAL_SHARE_IRQ=y
# CONFIG_SERIAL_DETECT_IRQ is not set
CONFIG_SERIAL_MULTIPOINT=y
CONFIG_HUB6=y
CONFIG_SERIAL_NONSTANDARD=y
CONFIG_COMPUTONE=m
CONFIG_ROCKETPORT=m
CONFIG_CYCLADES=m
# CONFIG_CYZ_INTR is not set
CONFIG_DIGIEPCA=m
CONFIG_ESPSERIAL=m
CONFIG_MOXA_INTELLIO=m
CONFIG_MOXA_SMARTIO=m
CONFIG_ISI=m
CONFIG_SYNCLINK=m
CONFIG_SYNCLINKMP=m
CONFIG_N_HDLC=m
CONFIG_RISCOM8=m
CONFIG_SPECIALIX=m
# CONFIG_SPECIALIX_RTSCCTS is not set
CONFIG_SX=m
CONFIG_RIO=m
# CONFIG_RIO_OLDPCI is not set
CONFIG_STALDRV=y
CONFIG_STALLION=m
CONFIG_ISTALLION=m
CONFIG_UNIX98_PTYS=y
CONFIG_UNIX98_PTY_COUNT=256
CONFIG_PRINTER=m
# CONFIG_LP_CONSOLE is not set
CONFIG_PPDEV=m
CONFIG_TIPAR=m

#
# I2C support
#
CONFIG_I2C=m
CONFIG_I2C_ALGOBIT=m
CONFIG_I2C_PHILIPSPAR=m
CONFIG_I2C_ELV=m
CONFIG_I2C_VELLEMAN=m
CONFIG_SCx200_I2C=m
CONFIG_SCx200_I2C_SCL=12
CONFIG_SCx200_I2C_SDA=13
CONFIG_SCx200_ACB=m
CONFIG_I2C_ALGOPCF=m
CONFIG_I2C_ELEKTOR=m
CONFIG_I2C_CHARDEV=m
CONFIG_I2C_PROC=m

#
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
# Mice
#
CONFIG_BUSMOUSE=m
CONFIG_ATIXL_BUSMOUSE=m
CONFIG_LOGIBUSMOUSE=m
CONFIG_MS_BUSMOUSE=m
CONFIG_MOUSE=m
CONFIG_PSMOUSE=y
CONFIG_82C710_MOUSE=m
CONFIG_PC110_PAD=m
CONFIG_MK712_MOUSE=m

#
# Joysticks
#
CONFIG_INPUT_GAMEPORT=m
CONFIG_INPUT_NS558=m
CONFIG_INPUT_LIGHTNING=m
CONFIG_INPUT_PCIGAME=m
CONFIG_INPUT_CS461X=m
CONFIG_INPUT_EMU10K1=m
CONFIG_INPUT_SERIO=m
CONFIG_INPUT_SERPORT=m

#
# Joysticks
#
CONFIG_INPUT_ANALOG=m
CONFIG_INPUT_A3D=m
CONFIG_INPUT_ADI=m
CONFIG_INPUT_COBRA=m
CONFIG_INPUT_GF2K=m
CONFIG_INPUT_GRIP=m
CONFIG_INPUT_INTERACT=m
CONFIG_INPUT_TMDC=m
CONFIG_INPUT_SIDEWINDER=m
CONFIG_INPUT_IFORCE_USB=m
CONFIG_INPUT_IFORCE_232=m
CONFIG_INPUT_WARRIOR=m
CONFIG_INPUT_MAGELLAN=m
CONFIG_INPUT_SPACEORB=m
CONFIG_INPUT_SPACEBALL=m
CONFIG_INPUT_STINGER=m
CONFIG_INPUT_DB9=m
CONFIG_INPUT_GAMECON=m
CONFIG_INPUT_TURBOGRAFX=m
CONFIG_QIC02_TAPE=m
CONFIG_QIC02_DYNCONF=y

#
# Setting runtime QIC-02 configuration is done with qic02conf
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
#  
  
#  
# from the tpqic02-support package. It is available at  
#  
  
#  
# metalab.unc.edu or ftp://titus.cfw.com/pub/Linux/util/  
#  
CONFIG_IPMI_HANDLER=m  
# CONFIG_IPMI_PANIC_EVENT is not set  
CONFIG_IPMI_DEVICE_INTERFACE=m  
CONFIG_IPMI_KCS=m  
CONFIG_IPMI_WATCHDOG=m  
  
#  
# Watchdog Cards  
#  
CONFIG_WATCHDOG=y  
# CONFIG_WATCHDOG_NOWAYOUT is not set  
CONFIG_ACQUIRE_WDT=m  
CONFIG_ADVANTECH_WDT=m  
CONFIG_ALIM1535_WDT=m  
CONFIG_ALIM7101_WDT=m  
CONFIG_SC520_WDT=m  
CONFIG_PCWATCHDOG=m  
CONFIG_EUROTECH_WDT=m  
CONFIG_IB700_WDT=m  
CONFIG_WAFER_WDT=m  
CONFIG_I810_TCO=m  
CONFIG_MIXCOMWD=m  
CONFIG_60XX_WDT=m  
CONFIG_SC1200_WDT=m  
CONFIG_SCx200_WDT=m  
CONFIG_SOFT_WATCHDOG=m  
CONFIG_W83877F_WDT=m  
CONFIG_WDT=m  
CONFIG_WDTPCI=m  
CONFIG_WDT_501=y  
# CONFIG_WDT_501_FAN is not set  
CONFIG_MACHZ_WDT=m  
CONFIG_SCx200=m  
CONFIG_SCx200_GPIO=m  
CONFIG_AMD_RNG=m  
CONFIG_INTEL_RNG=m  
CONFIG_HW_RANDOM=m  
CONFIG_AMD_PM768=m  
CONFIG_NVRAM=m  
CONFIG_RTC=m  
CONFIG_DTLK=m  
CONFIG_R3964=m
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_APPLICOM=m
CONFIG_SONYPI=m

#
# Ftape, the floppy tape device driver
#
CONFIG_FTAPE=m
CONFIG_ZFTAPE=m
CONFIG_ZFT_DFLT_BLK_SZ=10240

#
# The compressor will be built as a module only!
#
CONFIG_ZFT_COMPRESSOR=m
CONFIG_FT_NR_BUFFERS=3
CONFIG_FT_PROC_FS=y
CONFIG_FT_NORMAL_DEBUG=y
# CONFIG_FT_FULL_DEBUG is not set
# CONFIG_FT_NO_TRACE is not set
# CONFIG_FT_NO_TRACE_AT_ALL is not set

#
# Hardware configuration
#
CONFIG_FT_STD_FDC=y
# CONFIG_FT_MACH2 is not set
# CONFIG_FT_PROBE_FC10 is not set
# CONFIG_FT_ALT_FDC is not set
CONFIG_FT_FDC_THR=8
CONFIG_FT_FDC_MAX_RATE=2000
CONFIG_FT_ALPHA_CLOCK=0
CONFIG_AGP=m
CONFIG_AGP_INTEL=y
CONFIG_AGP_I810=y
CONFIG_AGP_VIA=y
CONFIG_AGP_AMD=y
CONFIG_AGP_AMD_K8=y
CONFIG_AGP_SIS=y
CONFIG_AGP_ALI=y
CONFIG_AGP_SWORKS=y
CONFIG_AGP_NVIDIA=y
CONFIG_AGP_ATI=y

#
# Direct Rendering Manager (XFree86 DRI support)
#
CONFIG_DRM=y
# CONFIG_DRM_OLD is not set

#
# DRM 4.1 drivers
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
#
CONFIG_DRM_NEW=y
CONFIG_DRM_TDFX=m
CONFIG_DRM_GAMMA=m
CONFIG_DRM_R128=m
CONFIG_DRM_RADEON=m
CONFIG_DRM_I810=m
# CONFIG_DRM_I810_XFREE_41 is not set
CONFIG_DRM_I830=m
CONFIG_DRM_MGA=m
CONFIG_DRM_SIS=m
```

```
#
# PCMCIA character devices
#
CONFIG_PCMCIA_SERIAL_CS=m
CONFIG_SYNCLINK_CS=m
CONFIG_MWAVE=m
CONFIG_OBMOUSE=m
```

```
#
# Multimedia devices
#
CONFIG_VIDEO_DEV=m
```

```
#
# Video For Linux
#
CONFIG_VIDEO_PROC_FS=y
CONFIG_I2C_PARPORT=m
```

```
#
# Video Adapters
#
CONFIG_VIDEO_BT848=m
CONFIG_VIDEO_PMS=m
CONFIG_VIDEO_BWQCAM=m
CONFIG_VIDEO_CQCAM=m
CONFIG_VIDEO_W9966=m
CONFIG_VIDEO_CPIA=m
CONFIG_VIDEO_CPIA_PP=m
CONFIG_VIDEO_CPIA_USB=m
CONFIG_VIDEO_SAA5249=m
CONFIG_TUNER_3036=m
CONFIG_VIDEO_STRADIS=m
CONFIG_VIDEO_ZORAN=m
CONFIG_VIDEO_ZORAN_BUZ=m
CONFIG_VIDEO_ZORAN_DC10=m
CONFIG_VIDEO_ZORAN_LML33=m
CONFIG_VIDEO_ZR36120=m
CONFIG_VIDEO_MEYE=m
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
#
# Radio Adapters
#
CONFIG_RADIO_CADET=m
CONFIG_RADIO_RTRACK=m
CONFIG_RADIO_RTRACK2=m
CONFIG_RADIO_AZTECH=m
CONFIG_RADIO_GEMTEK=m
CONFIG_RADIO_GEMTEK_PCI=m
CONFIG_RADIO_MAXIRADIO=m
CONFIG_RADIO_MAESTRO=m
CONFIG_RADIO_MIROPCM20=m
CONFIG_RADIO_MIROPCM20_RDS=m
CONFIG_RADIO_SF16FMI=m
CONFIG_RADIO_SF16FMR2=m
CONFIG_RADIO_TERRATEC=m
CONFIG_RADIO_TRUST=m
CONFIG_RADIO_TYPHOON=m
CONFIG_RADIO_TYPHOON_PROC_FS=y
CONFIG_RADIO_ZOLTRIX=m

#
# File systems
#
CONFIG_QUOTA=y
CONFIG_QFMT_V2=m
CONFIG_AUTOFS_FS=m
CONFIG_AUTOFS4_FS=m
CONFIG_REISERFS_FS=m
# CONFIG_REISERFS_CHECK is not set
# CONFIG_REISERFS_PROC_INFO is not set
CONFIG_ADFS_FS=m
# CONFIG_ADFS_FS_RW is not set
CONFIG_AFFS_FS=m
CONFIG_HFS_FS=m
CONFIG_HFSPLUS_FS=m
CONFIG_BEFS_FS=m
# CONFIG_BEFS_DEBUG is not set
CONFIG_BFS_FS=m
CONFIG_EXT3_FS=m
CONFIG_JBD=m
# CONFIG_JBD_DEBUG is not set
CONFIG_FAT_FS=m
CONFIG_MSDOS_FS=m
CONFIG_UMSDOS_FS=m
CONFIG_VFAT_FS=m
CONFIG_EFS_FS=m
# CONFIG_JFFS_FS is not set
# CONFIG_JFFS2_FS is not set
CONFIG_CRAMFS=y
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_TMPFS=y
CONFIG_RAMFS=y
CONFIG_ISO9660_FS=m
CONFIG_JOLIET=y
CONFIG_ZISOFS=y
CONFIG_JFS_FS=m
# CONFIG_JFS_DEBUG is not set
CONFIG_JFS_STATISTICS=y
CONFIG_MINIX_FS=m
CONFIG_VXFS_FS=m
CONFIG_NTFS_FS=m
# CONFIG_NTFS_RW is not set
CONFIG_HPFS_FS=m
CONFIG_PROC_FS=y
CONFIG_DEVFS_FS=y
# CONFIG_DEVFS_MOUNT is not set
# CONFIG_DEVFS_DEBUG is not set
CONFIG_DEVPTS_FS=y
CONFIG_QNX4FS_FS=m
# CONFIG_QNX4FS_RW is not set
CONFIG_ROMFS_FS=m
CONFIG_EXT2_FS=y
CONFIG_SYSV_FS=m
CONFIG_UDF_FS=m
# CONFIG_UDF_RW is not set
CONFIG_UFS_FS=m
# CONFIG_UFS_FS_WRITE is not set
CONFIG_XFS_FS=m
CONFIG_XFS_QUOTA=y
# CONFIG_XFS_RT is not set
# CONFIG_XFS_TRACE is not set
# CONFIG_XFS_DEBUG is not set

#
# Network File Systems
#
CONFIG_CODA_FS=m
CONFIG_INTERMEZZO_FS=m
CONFIG_NFS_FS=m
CONFIG_NFS_V3=y
CONFIG_NFS_DIRECTIO=y
# CONFIG_ROOT_NFS is not set
CONFIG_NFSD=m
CONFIG_NFSD_V3=y
CONFIG_NFSD_TCP=y
CONFIG_SUNRPC=m
CONFIG_LOCKD=m
CONFIG_LOCKD_V4=y
CONFIG_SMB_FS=m
# CONFIG_SMB_NLS_DEFAULT is not set
CONFIG_SMB_UNIX=y
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_NCP_FS=m
# CONFIG_NCPFS_PACKET_SIGNING is not set
# CONFIG_NCPFS_IOCTL_LOCKING is not set
# CONFIG_NCPFS_STRONG is not set
CONFIG_NCPFS_NFS_NS=y
CONFIG_NCPFS_OS2_NS=y
# CONFIG_NCPFS_SMALLDOS is not set
CONFIG_NCPFS_NLS=y
CONFIG_NCPFS_EXTRAS=y
CONFIG_ZISOFS_FS=m

#
# Partition Types
#
CONFIG_PARTITION_ADVANCED=y
CONFIG_ACORN_PARTITION=y
CONFIG_ACORN_PARTITION_ICS=y
# CONFIG_ACORN_PARTITION_ADFS is not set
# CONFIG_ACORN_PARTITION_POWERTEC is not set
CONFIG_ACORN_PARTITION_RISCIX=y
CONFIG_OSF_PARTITION=y
CONFIG_AMIGA_PARTITION=y
CONFIG_ATARI_PARTITION=y
CONFIG_MAC_PARTITION=y
CONFIG_MSDOS_PARTITION=y
CONFIG_BSD_DISKLABEL=y
CONFIG_MINIX_SUBPARTITION=y
CONFIG_SOLARIS_X86_PARTITION=y
CONFIG_UNIXWARE_DISKLABEL=y
CONFIG_LDM_PARTITION=y
# CONFIG_LDM_DEBUG is not set
CONFIG_SGI_PARTITION=y
CONFIG_ULTRIX_PARTITION=y
CONFIG_SUN_PARTITION=y
# CONFIG_EFI_PARTITION is not set
CONFIG_SMB_NLS=y
CONFIG_NLS=y

#
# Native Language Support
#
CONFIG_NLS_DEFAULT="cp437"
CONFIG_NLS_CODEPAGE_437=m
CONFIG_NLS_CODEPAGE_737=m
CONFIG_NLS_CODEPAGE_775=m
CONFIG_NLS_CODEPAGE_850=m
CONFIG_NLS_CODEPAGE_852=m
CONFIG_NLS_CODEPAGE_855=m
CONFIG_NLS_CODEPAGE_857=m
CONFIG_NLS_CODEPAGE_860=m
CONFIG_NLS_CODEPAGE_861=m
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_NLS_CODEPAGE_862=m
CONFIG_NLS_CODEPAGE_863=m
CONFIG_NLS_CODEPAGE_864=m
CONFIG_NLS_CODEPAGE_865=m
CONFIG_NLS_CODEPAGE_866=m
CONFIG_NLS_CODEPAGE_869=m
CONFIG_NLS_CODEPAGE_936=m
CONFIG_NLS_CODEPAGE_950=m
CONFIG_NLS_CODEPAGE_932=m
CONFIG_NLS_CODEPAGE_949=m
CONFIG_NLS_CODEPAGE_874=m
CONFIG_NLS_ISO8859_8=m
CONFIG_NLS_CODEPAGE_1250=m
CONFIG_NLS_CODEPAGE_1251=m
CONFIG_NLS_ISO8859_1=m
CONFIG_NLS_ISO8859_2=m
CONFIG_NLS_ISO8859_3=m
CONFIG_NLS_ISO8859_4=m
CONFIG_NLS_ISO8859_5=m
CONFIG_NLS_ISO8859_6=m
CONFIG_NLS_ISO8859_7=m
CONFIG_NLS_ISO8859_9=m
CONFIG_NLS_ISO8859_13=m
CONFIG_NLS_ISO8859_14=m
CONFIG_NLS_ISO8859_15=m
CONFIG_NLS_KOI8_R=m
CONFIG_NLS_KOI8_U=m
CONFIG_NLS_UTF8=m

#
# Console drivers
#
CONFIG_VGA_CONSOLE=y
CONFIG_VIDEO_SELECT=y
CONFIG_MDA_CONSOLE=m

#
# Frame-buffer support
#
CONFIG_FB=y
CONFIG_DUMMY_CONSOLE=y
CONFIG_FB_RIVA=m
CONFIG_FB_CLGEN=m
CONFIG_FB_PM2=m
# CONFIG_FB_PM2_FIFO_DISCONNECT is not set
# CONFIG_FB_PM2_PCI is not set
CONFIG_FB_PM3=m
CONFIG_FB_CYBER2000=m
CONFIG_FB_VESA=y
CONFIG_FB_VGA16=m
CONFIG_FB_HGA=m
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_VIDEO_SELECT=y
CONFIG_FB_MATROX=m
CONFIG_FB_MATROX_MILLENIUM=y
CONFIG_FB_MATROX_MYSTIQUE=y
CONFIG_FB_MATROX_G450=y
CONFIG_FB_MATROX_G100=y
CONFIG_FB_MATROX_I2C=m
CONFIG_FB_MATROX_MAVEN=m
CONFIG_FB_MATROX_PROC=m
CONFIG_FB_MATROX_MULTHEAD=y
CONFIG_FB_ATY=m
CONFIG_FB_ATY_GX=y
CONFIG_FB_ATY_CT=y
CONFIG_FB_ATY_GENERIC_LCD=y
CONFIG_FB_RADEON=m
CONFIG_FB_ATY128=m
CONFIG_FB_INTEL=m
CONFIG_FB_SIS=m
CONFIG_FB_SIS_300=y
CONFIG_FB_SIS_315=y
CONFIG_FB_NEOMAGIC=m
CONFIG_FB_3DFX=m
CONFIG_FB_VOODOO1=m
# CONFIG_FB_TRIDENT is not set
CONFIG_FB_IT8181=m
CONFIG_FB_VIRTUAL=m
CONFIG_FBCON_ADVANCED=y
CONFIG_FBCON_MFB=m
CONFIG_FBCON_CFB2=m
CONFIG_FBCON_CFB4=m
CONFIG_FBCON_CFB8=m
CONFIG_FBCON_CFB16=m
CONFIG_FBCON_CFB24=m
CONFIG_FBCON_CFB32=m
# CONFIG_FBCON_AFB is not set
# CONFIG_FBCON_ILBM is not set
# CONFIG_FBCON_IPLAN2P2 is not set
# CONFIG_FBCON_IPLAN2P4 is not set
# CONFIG_FBCON_IPLAN2P8 is not set
# CONFIG_FBCON_MAC is not set
CONFIG_FBCON_VGA_PLANES=m
CONFIG_FBCON_VGA=m
CONFIG_FBCON_HGA=m
# CONFIG_FBCON_FONTWIDTH8_ONLY is not set
# CONFIG_FBCON_FONTS is not set
CONFIG_FONT_8x8=y
CONFIG_FONT_8x16=y

#
# Sound
#
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_SOUND=m
CONFIG_SOUND_ALI5455=m
CONFIG_SOUND_ALI5455_CODECCSPDIFOUT_PCMOUTSHARE=y
CONFIG_SOUND_ALI5455_CODECCSPDIFOUT_CODECCINDEPENDENTDMA=y
CONFIG_SOUND_ALI5455_CONTROLLERSPDIFOUT_PCMOUTSHARE=y
CONFIG_SOUND_ALI5455_CONTROLLERSPDIFOUT_CONTROLLERINDEPENDENTDMA=y
CONFIG_SOUND_BT878=m
CONFIG_SOUND_CMPCI=m
# CONFIG_SOUND_CMPCI_FM is not set
# CONFIG_SOUND_CMPCI_MIDI is not set
CONFIG_SOUND_CMPCI_JOYSTICK=y
CONFIG_SOUND_CMPCI_CM8738=y
# CONFIG_SOUND_CMPCI_SPDIFINVERSE is not set
# CONFIG_SOUND_CMPCI_SPDIFLOOP is not set
CONFIG_SOUND_CMPCI_SPEAKERS=2
CONFIG_SOUND_EMU10K1=m
CONFIG_MIDI_EMU10K1=y
CONFIG_SOUND_FUSION=m
CONFIG_SOUND_CS4281=m
CONFIG_SOUND_ES1370=m
CONFIG_SOUND_ES1371=m
CONFIG_SOUND_ESSSOLO1=m
CONFIG_SOUND_MAESTRO=m
CONFIG_SOUND_MAESTRO3=m
CONFIG_SOUND_FORTE=m
CONFIG_SOUND_ICH=m
CONFIG_SOUND_RME96XX=m
CONFIG_SOUND_SONICVIBES=m
CONFIG_SOUND_TRIDENT=m
CONFIG_SOUND_MSNDCLAS=m
# CONFIG_MSNDCLAS_HAVE_BOOT is not set
CONFIG_MSNDCLAS_INIT_FILE="/etc/sound/msndinit.bin"
CONFIG_MSNDCLAS_PERM_FILE="/etc/sound/msndperm.bin"
CONFIG_SOUND_MSNDPIN=m
# CONFIG_MSNDPIN_HAVE_BOOT is not set
CONFIG_MSNDPIN_INIT_FILE="/etc/sound/pndspini.bin"
CONFIG_MSNDPIN_PERM_FILE="/etc/sound/pndspem.bin"
CONFIG_SOUND_VIA82CXXX=m
CONFIG_MIDI_VIA82CXXX=y
CONFIG_SOUND_OSS=m
# CONFIG_SOUND_TRACEINIT is not set
# CONFIG_SOUND_DMAP is not set
CONFIG_SOUND_AD1816=m
CONFIG_SOUND_AD1889=m
CONFIG_SOUND_SGALAXY=m
CONFIG_SOUND_ADLIB=m
CONFIG_SOUND_ACI_MIXER=m
CONFIG_SOUND_CS4232=m
CONFIG_SOUND_SSCAPE=m
CONFIG_SOUND_GUS=m
CONFIG_SOUND_GUS16=y
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_SOUND_GUSMAX=y
CONFIG_SOUND_VMIDI=m
CONFIG_SOUND_TRIX=m
CONFIG_SOUND_MSS=m
CONFIG_SOUND_MPU401=m
CONFIG_SOUND_NM256=m
CONFIG_SOUND_MAD16=m
CONFIG_MAD16_OLDCARD=y
CONFIG_SOUND_PAS=m
# CONFIG_PAS_JOYSTICK is not set
CONFIG_SOUND_PSS=m
CONFIG_PSS_MIXER=y
# CONFIG_PSS_HAVE_BOOT is not set
CONFIG_SOUND_SB=m
CONFIG_SOUND_AWE32_SYNTH=m
CONFIG_SOUND_KAHLUA=m
CONFIG_SOUND_WAVEFRONT=m
CONFIG_SOUND_MAUI=m
CONFIG_SOUND_YM3812=m
CONFIG_SOUND_OPL3SA1=m
CONFIG_SOUND_OPL3SA2=m
CONFIG_SOUND_YMFPCI=m
# CONFIG_SOUND_YMFPCI_LEGACY is not set
CONFIG_SOUND_UART6850=m
CONFIG_SOUND_AEDSP16=m
CONFIG_SC6600=y
CONFIG_SC6600_JOY=y
CONFIG_SC6600_CDROM=4
CONFIG_SC6600_CDROMBASE=0x0
# CONFIG_AEDSP16_SBPRO is not set
# CONFIG_AEDSP16_MSS is not set
# CONFIG_AEDSP16_MPU401 is not set
CONFIG_SOUND_TVMIXER=m
CONFIG_SOUND_AD1980=m
CONFIG_SOUND_WM97XX=m

#
# USB support
#
CONFIG_USB=m
# CONFIG_USB_DEBUG is not set

#
# Miscellaneous USB options
#
CONFIG_USB_DEVICEFS=y
CONFIG_USB_BANDWIDTH=y

#
# USB Host Controller Drivers
#
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_USB_EHCI_HCD=m
CONFIG_USB_UHCI=m
CONFIG_USB_UHCI_ALT=m
CONFIG_USB_OHCI=m
CONFIG_USB_SL811HS_ALT=m
CONFIG_USB_SL811HS=m

#
# USB Device Class drivers
#
CONFIG_USB_AUDIO=m
CONFIG_USB_EMI26=m

#
# USB Bluetooth can only be used with disabled Bluetooth subsystem
#
CONFIG_USB_MIDI=m
CONFIG_USB_STORAGE=m
# CONFIG_USB_STORAGE_DEBUG is not set
CONFIG_USB_STORAGE_DATAFAB=y
CONFIG_USB_STORAGE_FREECOM=y
CONFIG_USB_STORAGE_ISD200=y
CONFIG_USB_STORAGE_DPCM=y
CONFIG_USB_STORAGE_HP8200e=y
CONFIG_USB_STORAGE_SDDR09=y
CONFIG_USB_STORAGE_SDDR55=y
CONFIG_USB_STORAGE_JUMPSHOT=y
CONFIG_USB_ACM=m
CONFIG_USB_PRINTER=m

#
# USB Human Interface Devices (HID)
#
CONFIG_USB_HID=m
CONFIG_USB_HIDINPUT=y
CONFIG_USB_HIDDEV=y
CONFIG_USB_KBD=m
CONFIG_USB_MOUSE=m
CONFIG_USB_AIPTEK=m
CONFIG_USB_WACOM=m
CONFIG_USB_KBTAB=m
CONFIG_USB_POWERMATE=m

#
# USB Imaging devices
#
CONFIG_USB_DC2XX=m
CONFIG_USB_MDC800=m
CONFIG_USB_SCANNER=m
CONFIG_USB_MICROTEK=m
CONFIG_USB_HPUSBSCSI=m
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
#
# USB Multimedia devices
#
CONFIG_USB_IBMCAM=m
CONFIG_USB_KONICAWC=m
CONFIG_USB_OV511=m
CONFIG_USB_PWC=m
CONFIG_USB_SE401=m
CONFIG_USB_STV680=m
CONFIG_USB_W9968CF=m
CONFIG_USB_VICAM=m
CONFIG_USB_DSBR=m
CONFIG_USB_DABUSB=m

#
# USB Network adaptors
#
CONFIG_USB_PEGASUS=m
CONFIG_USB_RTL8150=m
CONFIG_USB_KAWETH=m
CONFIG_USB_CATC=m
CONFIG_USB_CDCETHER=m
CONFIG_USB_USBNET=m

#
# USB port drivers
#
CONFIG_USB_USS720=m

#
# USB Serial Converter support
#
CONFIG_USB_SERIAL=m
# CONFIG_USB_SERIAL_DEBUG is not set
CONFIG_USB_SERIAL_GENERIC=y
CONFIG_USB_SERIAL_BELKIN=m
CONFIG_USB_SERIAL_WHITEHEAT=m
CONFIG_USB_SERIAL_DIGI_ACCELEPORT=m
CONFIG_USB_SERIAL_EMPEG=m
CONFIG_USB_SERIAL_FTDI_SIO=m
CONFIG_USB_SERIAL_VISOR=m
CONFIG_USB_SERIAL_IPAQ=m
CONFIG_USB_SERIAL_IR=m
CONFIG_USB_SERIAL_EDGEPORT=m
CONFIG_USB_SERIAL_EDGEPORT_TI=m
CONFIG_USB_SERIAL_KEYSPAN_PDA=m
CONFIG_USB_SERIAL_KEYSPAN=m
CONFIG_USB_SERIAL_KEYSPAN_USA28=y
CONFIG_USB_SERIAL_KEYSPAN_USA28X=y
CONFIG_USB_SERIAL_KEYSPAN_USA28XA=y
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_USB_SERIAL_KEYSPAN_USA28XB=y
CONFIG_USB_SERIAL_KEYSPAN_USA19=y
CONFIG_USB_SERIAL_KEYSPAN_USA18X=y
CONFIG_USB_SERIAL_KEYSPAN_USA19W=y
CONFIG_USB_SERIAL_KEYSPAN_USA19QW=y
CONFIG_USB_SERIAL_KEYSPAN_USA19QI=y
CONFIG_USB_SERIAL_KEYSPAN_MPR=y
CONFIG_USB_SERIAL_KEYSPAN_USA49W=y
CONFIG_USB_SERIAL_KEYSPAN_USA49WLC=y
CONFIG_USB_SERIAL_MCT_U232=m
CONFIG_USB_SERIAL_KLSI=m
CONFIG_USB_SERIAL_KOBIL_SCT=m
CONFIG_USB_SERIAL_PL2303=m
CONFIG_USB_SERIAL_CYBERJACK=m
CONFIG_USB_SERIAL_XIRCOM=m
CONFIG_USB_SERIAL_OMNINET=m
```

```
#
# USB Miscellaneous drivers
#
CONFIG_USB_RIO500=m
CONFIG_USB_AUERSWALD=m
CONFIG_USB_TIGL=m
CONFIG_USB_BRLVGER=m
CONFIG_USB_LCD=m
CONFIG_USB_SPEEDTOUCH=m
```

```
#
# Support for USB gadgets
#
# CONFIG_USB_GADGET is not set
```

```
#
# Bluetooth support
#
CONFIG_BLUEZ=m
CONFIG_BLUEZ_L2CAP=m
CONFIG_BLUEZ_SCO=m
CONFIG_BLUEZ_RFCOMM=m
CONFIG_BLUEZ_RFCOMM_TTY=y
CONFIG_BLUEZ_BNEP=m
CONFIG_BLUEZ_BNEP_MC_FILTER=y
CONFIG_BLUEZ_BNEP_PROTO_FILTER=y
CONFIG_BLUEZ_CMTP=m
```

```
#
# Bluetooth device drivers
#
CONFIG_BLUEZ_HCIUSB=m
CONFIG_BLUEZ_HCIUSB_SCO=y
CONFIG_BLUEZ_HCIUART=m
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

```
CONFIG_BLUEZ_HCIUART_H4=y
CONFIG_BLUEZ_HCIUART_BCSP=y
# CONFIG_BLUEZ_HCIUART_BCSP_TXCRC is not set
CONFIG_BLUEZ_HCIBFUSB=m
CONFIG_BLUEZ_HCIDTL1=m
CONFIG_BLUEZ_HCIBT3C=m
CONFIG_BLUEZ_HCIBLUECARD=m
CONFIG_BLUEZ_HCIBTUART=m
CONFIG_BLUEZ_HCIVHCI=m
```

```
#
# Kernel hacking
#
CONFIG_DEBUG_KERNEL=y
# CONFIG_DEBUG_STACKOVERFLOW is not set
# CONFIG_DEBUG_HIGHMEM is not set
# CONFIG_DEBUG_SLAB is not set
# CONFIG_DEBUG_IOVIRT is not set
CONFIG_MAGIC_SYSRQ=y
# CONFIG_DEBUG_SPINLOCK is not set
# CONFIG_FRAME_POINTER is not set
CONFIG_LOG_BUF_SHIFT=0
```

```
#
# Cryptographic options
#
CONFIG_CRYPT=y
CONFIG_CRYPT_HMAC=y
CONFIG_CRYPT_NULL=m
CONFIG_CRYPT_MD4=m
CONFIG_CRYPT_MD5=y
CONFIG_CRYPT_SHA1=y
CONFIG_CRYPT_SHA256=m
CONFIG_CRYPT_SHA512=m
CONFIG_CRYPT_WP512=m
CONFIG_CRYPT_DES=y
CONFIG_CRYPT_BLOWFISH=m
CONFIG_CRYPT_TWOFISH=m
CONFIG_CRYPT_SERPENT=m
CONFIG_CRYPT_AES=m
CONFIG_CRYPT_CAST5=m
CONFIG_CRYPT_CAST6=m
CONFIG_CRYPT_TEA=m
CONFIG_CRYPT_KHAZAD=m
CONFIG_CRYPT_ANUBIS=m
CONFIG_CRYPT_ARC4=m
CONFIG_CRYPT_DEFLATE=y
CONFIG_CRYPT_MICHAEL_MIC=m
CONFIG_CRYPT_TEST=m
```

```
#
```

[BUG] ide-core reports missing symbol init_cmd640_vlb

[BUG] ide-core reports missing symbol init_cmd640_vlb

Library routines

#

CONFIG_CRC32=m

CONFIG_ZLIB_INFLATE=y

CONFIG_ZLIB_DEFLATE=y

CONFIG_FW_LOADER=m