

[patch 08/12] syslets: x86, add move_user_context() method

Source: <http://linux.derkeiler.com/Mailing-Lists/Kernel/2007-02/msg10246.html>

- *From:* Ingo Molnar <mingo@xxxxxxx>
 - *Date:* Wed, 28 Feb 2007 22:42:04 +0100
-

From: Ingo Molnar <mingo@xxxxxxx>

add the move_user_context() method to move the user-space context of one kernel thread to another kernel thread.

User-space might notice the changed TID, but execution, stack and register contents (general purpose and FPU) are still the same.

An architecture must implement this interface before it can turn CONFIG_ASYNC_SUPPORT on.

Signed-off-by: Ingo Molnar <mingo@xxxxxxx>

Signed-off-by: Arjan van de Ven <arjan@xxxxxxxxxxxxxxxxxx>

arch/i386/kernel/process.c | 21 +++++
include/asm-i386/system.h | 7 +++++
2 files changed, 28 insertions(+)

Index: linux/arch/i386/kernel/process.c

```
=====
--- linux.orig/arch/i386/kernel/process.c
+++ linux/arch/i386/kernel/process.c
@@ -839,6 +839,27 @@ unsigned long get_wchan(struct task_stru
 }

/*
+ * Move user-space context from one kernel thread to another.
+ * This includes registers and FPU state. Callers must make
+ * sure that neither task is running user context at the moment:
+ */
+void
+move_user_context(struct task_struct *new_task, struct task_struct *old_task)
+{
+ struct pt_regs *old_regs = task_pt_regs(old_task);
+ struct pt_regs *new_regs = task_pt_regs(new_task);
+ union i387_union *tmp;
+
+ *new_regs = *old_regs;
```

[patch 08/12] syslets: x86, add move_user_context() method

```
+ /*
+ * Flip around the FPU state too:
+ */
+ tmp = new_task->thread.i387;
+ new_task->thread.i387 = old_task->thread.i387;
+ old_task->thread.i387 = tmp;
+ }
+
+ /*
+ * sys_alloc_thread_area: get a yet unused TLS descriptor index.
+ */
static int get_free_idx(void)
Index: linux/include/asm-i386/system.h
=====
--- linux.orig/include/asm-i386/system.h
+++ linux/include/asm-i386/system.h
@@ -33,6 +33,13 @@ extern struct task_struct * FASTCALL(__s
"2" (prev), "d" (next)); \
} while (0)

+ /*
+ * Move user-space context from one kernel thread to another.
+ * This includes registers and FPU state for now:
+ */
+extern void
+move_user_context(struct task_struct *new_task, struct task_struct *old_task);
+
#define _set_base(addr,base) do { unsigned long __pr; \
__asm__ __volatile__ ("movw %%dx,%1\n\t" \
"rorl $16,%%edx\n\t" \
-
To unsubscribe from this list: send the line "unsubscribe linux-kernel" in
the body of a message to majordomo@xxxxxxxxxxxxxxxxxxx
More majordomo info at http://vger.kernel.org/majordomo-info.html
Please read the FAQ at http://www.tux.org/lkml/
```