

# shell scripting problem

**Source:** <http://linux.derkeiler.com/Mailing-Lists/RedHat/2004-04/1078.html>

---

**From:** MM\_Siddique (*mms\_at\_comnets.uni-bremen.de*)

**Date:** 04/30/04

Date: Fri, 30 Apr 2004 18:28:11 +0200

To: redhat-list@redhat.com

can anybody tell me the meaning of the following script part

```
# Any additions from configure.in:
ac_help="$ac_help
--with-opts-prefix=PREFIX Prefix where autoopts is installed (optional)"
ac_help="$ac_help
--with-opts-exec-prefix=PREFIX
Exec prefix where autoopts is installed (optional)"

# Check whether --with-opts-prefix or --without-opts-prefix was given.
if test "${with_opts_prefix+set}" = set; then
withval="$with_opts_prefix"
:
fi

# Check whether --with-opts-exec-prefix or --without-opts-exec-prefix
was given.
if test "${with_opts_exec_prefix+set}" = set; then
withval="$with_opts_exec_prefix"
:
fi

# Check whether --enable-opts-test or --disable-opts-test was given.
if test "${enable_opts_test+set}" = set; then
enableval="$enable_opts_test"
:
fi

if test x$with_opts_exec_prefix != x ; then
autoopts_config_args="$autoopts_config_args
--exec-prefix=$with_opts_exec_prefix"
if test x${AUTOOPTS_CONFIG+set} != xset ; then
AUTOOPTS_CONFIG=$with_opts_exec_prefix/bin/autoopts-config
fi
fi
if test x$with_opts_prefix != x ; then
```

## RedHat: shell scripting problem

```
autoopts_config_args="$autoopts_config_args --prefix=$with_opts_prefix"  
if test x${AUTOOPTS_CONFIG+set} != xset ; then  
AUTOOPTS_CONFIG=$with_opts_prefix/bin/autoopts-config  
fi  
fi
```

```
MSC – CIT Student{  
MohAMMad MuTTakin SiDDique < Himel >;  
University of Bremen, Germany:  
Email: mmshimel@yahoo.com;  
Tel(home) : ++49 421 896 0375;  
dept) : ++49 421 218 8251;  
Handy: ++49 0179 7716566;  
} mms;
```

```
--  
redhat-list mailing list  
unsubscribe mailto:redhat-list-request@redhat.com?subject=unsubscribe  
https://www.redhat.com/mailman/listinfo/redhat-list
```