

Re: how to setup the squid server

Source: <http://linux.derkeiler.com/Mailing-Lists/RedHat/2006-12/msg00381.html>

- *From:* "John O'Loughlin" <j.oloughlin@xxxxxxxxxxx>
 - *Date:* Wed, 27 Dec 2006 14:38:18 +0000 (GMT)
-

Hi

also, in the file `/etc/squid/squid.conf` under the `acl` section you will find:

```
# INSERT YOUR OWN RULE(S) HERE TO ALLOW ACCESS FROM YOUR CLIENTS
```

```
# Example rule allowing access from your local networks. Adapt
# to list your (internal) IP networks from where browsing should
# be allowed
#acl our_networks src 192.168.1.0/24 192.168.2.0/24
#http_access allow our_networks
```

You need to unhash the last two lines and then set the IP range to match you network, so it may be:

```
acl our_networks src 192.168.2.0/24
http_access allow our_networks
```

for example

squid will then accept connections from hosts with IP addresses in that range.

John

On Wed, 27 Dec 2006, tamer amr wrote:

hi

i want to configure the squid server for my local network

Do You Yahoo!?

Tired of spam? Yahoo! Mail has the best spam protection around

<http://mail.yahoo.com>

--

redhat-list mailing list

unsubscribe <mailto:redhat-list-request@xxxxxxxxxxx?subject=unsubscribe>

<https://www.redhat.com/mailman/listinfo/redhat-list>

Re: how to setup the squid server

--

redhat-list mailing list

unsubscribe <mailto:redhat-list-request@xxxxxxxxxx?subject=unsubscribe>

<https://www.redhat.com/mailman/listinfo/redhat-list>