

# Sendmail multiple domain

---

*Source:* <http://linux.derkeiler.com/Mailing-Lists/RedHat/2007-05/msg00279.html>

---

- *From:* "nilesh vaghela" <nileshj.vaghela@xxxxxxxx>
  - *Date:* Tue, 29 May 2007 18:34:53 +0530
- 

Dear All,

We have setup one sendmail server with mycompany.com at ABC place.

Now at XYZ place we need to set the server for mycompany.com only.

Now if when at XYZ user send a mail for user2@xxxxxxxxxxxxx as the user2 is not at XYZ is say unknown user. So i tried LUSER\_RELAY.

But mycompany.com resolve locally so it does not work.  
if I set the entry of LUSER\_RELAY to mycompany.com then it resolve locally.  
If I set the entry of LUSER\_RELAY to xx.xx.xx.xx ( ipaddress ) of ABC server then the mail will be delivered as user2@xxxxxxxxxxxxx

How to forward all the mail which is for non local user at XYZ to ABC place with correct name. ie. user2@xxxxxxxxxxxxx

--

Nilesh Vaghela  
ElectroMech  
Redhat Channel Partner and Training Partner  
74, Nalanda Complex, Satellite Rd, Ahmedabad  
25, The Emperor, Fatehgunj, Baroda.  
[www.electromech.info](http://www.electromech.info)

--

redhat-list mailing list  
unsubscribe <mailto:redhat-list-request@xxxxxxxx?subject=unsubscribe>  
<https://www.redhat.com/mailman/listinfo/redhat-list>