

## Fwd: RE: RE: RHEL4 and HP Proliant server

---

*Source:* <http://linux.derkeiler.com/Mailing-Lists/RedHat/2007-10/msg00247.html>

---

- *From:* <[m.roth2006@xxxxxxx](mailto:m.roth2006@xxxxxxx)>
  - *Date:* Tue, 23 Oct 2007 17:31:57 -0400 (EDT)
- 

And the guy here, Scott, responds:

Date: Tue, 23 Oct 2007 17:25:47 -0400  
From: "ELLIS, SCOTT, ATTSI" <[se816g@xxxxxxx](mailto:se816g@xxxxxxx)>

I believe we are g5 dl380. Also, I noted the closest driver on the CD which I noticed shared the same cciss reference and tried that. I proceeded to install the driver ... It did in fact come back and say no hard drives found... So the comments are on to something. So, why doesn't the redhat linux install prompt you to somehow build or create or otherwise the log / phy hard drives before proceeding ??

-----Original Message-----

From: [m.roth2006@xxxxxxx](mailto:m.roth2006@xxxxxxx) [<mailto:m.roth2006@xxxxxxx>]  
Sent: Tuesday, October 23, 2007 4:18 PM  
To: ELLIS, SCOTT, ATTSI  
Subject: Fwd: RE: RHEL4 and HP Proliant server

----- Original message -----

Date: Tue, 23 Oct 2007 15:05:47 -0400  
From: "Broekman, Maarten" <[Maarten.Broekman@xxxxxxx](mailto:Maarten.Broekman@xxxxxxx)>  
Subject: RE: RHEL4 and HP Proliant server  
To: "General Red Hat Linux discussion list" <[redhat-list@xxxxxxxxxxx](mailto:redhat-list@xxxxxxxxxxx)>

What generation of DL380? Which RHEL4 update? We have DL380s here (G2, G3, G4) and we can build off the boot CD without any problems.

Also, you need to make sure that you've created a logical drive on the hardware raid. If there are no logical drives on the hardware raid then there are 'technically' no hard drives. If you want to use LVM, then you would have to create each hard drive as it's own logical drive, though I'm not sure why you want to do that.

As Jeremy mentioned, it's definitely a cpqarray or cciss driver that

Fwd: RE: RE: RHEL4 and HP Proliant server

you're going to end up using, but that should be on the CDs already.

Maarten Broekman  
Email: maarten.broekman@xxxxxxx

-----Original Message-----

From: redhat-list-bounces@xxxxxxxxxxx  
[mailto:redhat-list-bounces@xxxxxxxxxxx] On Behalf Of Gaddis, Jeremy L.  
Sent: Tuesday, October 23, 2007 2:57 PM  
To: General Red Hat Linux discussion list  
Subject: Re: RHEL4 and HP Proliant server

On 10/23/07, m.roth2006@xxxxxxx <m.roth2006@xxxxxxx> wrote:

Ok, I've got a guy here – he's really a network guy, and he's trying

to put RHEL4 on a Proliant server, a DL380, I believe. It's \*all\* hardware RAID, and the std. RHEL4 CDs can't id the h/d. He's tried d/1 a package from HP, but that unzips to a file.dd, which I'm thinking needs to be dd'd to something....

Anyone have any ideas where he needs to go?

You'll most likely need either the cpqarray or cciss drivers. I have a pair of DL580's that are similar in hardware and that's the modules needed for RHEL4 to see the (hardware RAID) volumes.

The file.dd is probably a floppy disk image, which can be written to a floppy with "dd if=file.dd of=/dev/fd0". The drivers on that floppy can then be loaded during the installation process.

--  
Jeremy L. Gaddis  
<http://www.jeremygaddis.com/>

--  
redhat-list mailing list  
unsubscribe <mailto:redhat-list-request@xxxxxxxxxxx?subject=unsubscribe>  
<https://www.redhat.com/mailman/listinfo/redhat-list>

--  
redhat-list mailing list  
unsubscribe <mailto:redhat-list-request@xxxxxxxxxxx?subject=unsubscribe>  
<https://www.redhat.com/mailman/listinfo/redhat-list>

---

smime.p7s (6k bytes)

Fwd: RE: RE: RHEL4 and HP Proliant server

2

Fwd: RE: RE: RHEL4 and HP Proliant server

--

redhat-list mailing list

unsubscribe <mailto:redhat-list-request@xxxxxxxxxx?subject=unsubscribe>

<https://www.redhat.com/mailman/listinfo/redhat-list>