

Re: Block PC using Mac address in squid

Source: <http://linux.derkeiler.com/Mailing-Lists/RedHat/2008-01/msg00280.html>

- *From:* Cameron Simpson <cs@xxxxxxxxxx>
 - *Date:* Thu, 31 Jan 2008 10:31:47 +1100
-

On 30Jan2008 22:12, Mad Unix <madunix@xxxxxxxxxx> wrote:

```
|> | I tried as in /etc/squid/squid.conf
|> | acl block arp 00:13:45:d3:24:e4
|> | https_access deny block
|> | but it give me error as like: - (This is the output of # squid -k parse)
|> | aclParseAclLine: Invalid ACL type 'arp'
|> | FATAL: Bungled squid.conf line 1234: acl block arp 00:13:45:d3:24:e4
|> | squid Cache (Version 2.5.STABLE6): Terminated abnormally.
|>
|> The normal squid.conf describes the "arp" acl type and says:
|>
|> The arp ACL requires the special configure option --enable-arp-acl.
|>
|> So you will need to rebuild squid from source with this option.
|> Then you should be fine.
|
| question: i did the install of squid through yum , how can i add the MAC
| support in this case...
```

Fetch the squid source. Build with correct option and also
--prefix=/usr/local. Install. Run the new one and not the yum one.

And don't top post – it makes you look silly. English text reads down
the page, so replies belong on the BOTTOM of the post, under `_trimmed_`
quoted material.

—
Cameron Simpson <cs@xxxxxxxxxx> DoD#743
<http://www.cskk.ezoshosting.com/cs/>

"But of course my dear," I'd meant to say, "allow me to whisk you off
on my gleaming steed for a day of unparalleled wonders and delights."
But we both know it came out grudgingly along the lines of "Yeah
awright, who's gonna babysit?" – John Rooth, `_Two Wheels_` Nov96

—
redhat-list mailing list
unsubscribe <mailto:redhat-list-request@xxxxxxxxxx?subject=unsubscribe>
<https://www.redhat.com/mailman/listinfo/redhat-list>