

Re: Installing ATI Radeon video drivers on Redhat Advanced Server

Source: <http://linux.derkeiler.com/Newsgroups/comp.os.linux.misc/2004-01/3707.html>

linuxquestion_at_yahoo.com

Date: 01/31/04

Date: 30 Jan 2004 21:33:35 -0800

Here is the file: XF86Config

File generated by XConfigurator.

Refer to the XF86Config(4/5) man page for details about the format
of
this file.

Files section. This allows default font and rgb paths to be set

Section "Files"

The location of the RGB database. Note, this is the name of the
file minus the extension (like ".txt" or ".db"). There is normally
no need to change the default.

 RgbPath "/usr/X11R6/lib/X11/rgb"

Multiple FontPath entries are allowed (they are concatenated
together)
By default, Red Hat 6.0 and later now use a font server independent
of
the X server to render fonts.

 FontPath "unix:/7100"

EndSection

Server flags section.

Section "ServerFlags"

```
# Uncomment this to cause a core dump at the spot where a signal
is
# received. This may leave the console in an unusable state, but
may
# provide a better stack trace in the core dump to aid in
debugging
#NoTrapSignals
```

```
# Uncomment this to disable the <Ctrl><Alt><BS> server abort
sequence
# This allows clients to receive this key event.
#DontZap
```

```
# Uncomment this to disable the <Ctrl><Alt><KP_+>/<KP_-> mode
switching
# sequences. This allows clients to receive these key events.
#DontZoom
```

EndSection

```
# *****
# Input devices
# *****

# *****
# Keyboard section
# *****
```